



NOTES:

- 1. DUST CAPS ARE NOT SHOWN
- 2. PER CHANNEL @ 1310nm
IL <= 0.30dB
RL > 50dB
- 3. IF CABLE LENGTH IS LESS THAN 0.7M, CABLE SPLIT LENGTH IS 50MM FROM END OF THE BOOT.

885270106	SC-LC DUP SM 2MM 15M	15000(+200/-0)
885270105	SC-LC DUP SM 2MM 0.7M	700(+100/-0)
885270104	SC-LC DUP SM 2MM 10M	10000(+200/-0)
885270103	SC-LC DUP SM 2MM 5M	5000(+200/-0)
885270102	SC-LC DUP SM 2MM 3M	3000(+200/-0)
885270101	SC-LC DUP SM 2MM 2M	2000(+200/-0)
885270100	SC-LC DUP SM 2MM 1M	1000(+200/-0)
MX P/N	DESCRIPTION	LENGTH

ENTER DESCRIPTION EC NO: DG2009-0079 DRWN: XPCHEN CHKD: APPR: JOWANG	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		$\nabla = 0$ $\sphericalangle = 0$	mm	INCH	DRAWN BY XP	DATE 2008/10/23	TITLE SC-LC DUP SM 2MM				
			4 PLACES \pm ---	\pm ---	CHECKED BY LISA	DATE 2008/10/23					
			3 PLACES \pm ---	\pm ---	APPROVED BY JOHNNY	DATE 2008/10/23					
			2 PLACES \pm ---	\pm ---	MATERIAL NO.	DOCUMENT NO.	MOLEX INCORPORATED				
	1 PLACE \pm ---	\pm ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		ENTER PART		SD-88527-049		SHEET NO. 1 OF 00		