

## ATGBICS 10064-C network transceiver module Fiber optic 1000 Mbit/s SFP 1550 nm

Brand : ATGBICS

Product code: 10064-C

Product name : 10064-C

Extreme Compatible Transceiver SFP 1000Base-EZX 1550nm SMF 120km LC DOM

ATGBICS 10064-C network transceiver module Fiber optic 1000 Mbit/s SFP 1550 nm:

ATGBICS 10064 1000Base-EZX supports a distance of up to 120km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Extreme 10064= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 10064-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 1000 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 0.8 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *1000 Mbit/sInterface type *SFPSingle-mode fiber (SMF) supportedMulti-mode fiber (MMF) supportedXFiber optic connectorLCSFP transceiver standardZXMaximum transfer distance120000 mWavelength1550 nmEthernet LANEthernet interface typeFast EthernetDigital Diagnostics Monitoring (DDM)	1000 Mbit/s SFP	Country of origin Brand compatibility	United Kingdom Extreme Networks
		Power	
	× LC	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 0.8 W
		<b>Operational conditions</b>	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 95% 5 - 95%	
Wavelength-division multiplexing (WDM)	×	Weight & dimensions	
Features		Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 15 g
roduct colour Silver ousing material Metal lug and Play I			
Hot-Plug support	1	Packaging data	
Hot-swap Easy to install	4	Number of products included Package type	l pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.