

## Specification Sheet

Part Number: 126-00076



Design helps silence and stabilize the tie in high-vibration applications. Arrowhead-style mount provides low insertion and high extraction force.

Anti-rotational oval fastener forces bundle to travel in intended direction.

Rubber seal restricts water and debris from passing through mounting hole.

Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HS, Natural, 500/pkg

Article Number 126-00076

Type T60SOSSFT65x130-E-MD

Color Natural (NA)

Quantity Per bag

Product Description Push Mount Ties with Seal for Oval Holes provide a one-piece bundling and mounting solution. The oval arrowhead fastener won't rotate once inserted into a panel hole, ensuring proper routing of wires and hoses. The welded rubber seal protects against the ingress of water and debris.

Short Description Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HS, Natural, 500/pkg

Global Part Name T60SOSSFT65x130-E-MD-PA66HS-NA

Minimum Tensile Strength (Imperial)	67.0
Minimum Tensile Strength (Metric)	300
Length L (Imperial)	6.0
Length L (Metric)	157.6
Fixation Method	Arrowhead for oval holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.22
Width W (Metric)	5.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.18
Bundle Diameter Max (Metric)	30.0
Thickness T (Metric)	1.35

Panel Thickness Min (Imperial)	0.023
Panel Thickness Max (Imperial)	0.079
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.25 - 0.51
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm
Mounting Hole Diameter D Min (Imperial)	0.26
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0
Disc Diameter (Metric)	16.0 x 22.0
Disc Diameter (Imperial)	0.63 x 0.87
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988