HellermannTyton

Specification Sheet

Part Number: 156-02634



One-piece ratchet closure allows for easy installation during pre- or final assembly.

Easy release feature simplifies quick adjustments and maintenance.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

3M[™] VHB[™] adhesive on base creates an incredible bond with mountin(surface.

Inline Ratchet Clamp, 0.50" - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 250/ctn

Article Number156-02634TypeIRCBMB5AColorBlack (BK)

Quantity Per

bag

Product Description	The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.
Short Description	Inline Ratchet Clamp, 0.50" - 0.77" Bundle Dia, MB5A, PA66HIRHSUV, Black, 250/ctn
Global Part Name	IRCBMB5A-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	100.0
Minimum Tensile Strength (Metric)	445.0

- Length L (Imperial) 1.37
- Length L (Metric) 34.8
- Fixation Method Adhesive
- Width W (Imperial) 1.37
- Width W (Metric) 34.9
- Bundle Diameter Min (Imperial) 0.50
- Bundle Diameter Min (Metric) 12.70

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.56
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Adhesive	Acrylic
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250

© 2021 HellermannTyton. All Rights Reserved.