

Product Description

Max. Pull Tension:

Security & Sound Cable, Riser-CMR, 2-22 AWG stranded bare copper pairs with polyolefin insulation, PVC jacket with ripcord

Technical Specifications

Suitable Applications:			Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls						
Constru	uction Deta	ails							
Conducto	r								
Element	Number of El	lement	Size	Strand	ing	Material			
Pair(s)	2	2	22 AWG	7x30	BC	- Bare Copper			
nsulation									
Element	Material	N	om. Thie	ckness	Nom. Ir	sulation Dian	neter Color (Code	
Pair(s)	PP - Polyprop	ylene 0.0	008 in (0	.20 mm)	0.045 ir	(1.1 mm)	Black & Red, B	lack & White	
Outer Shie	eld								
Material									
No Shield	1								
	-								
Duter Jac		Nom T	Thicknes	Nor	n. Diame	ter Ripcord			
	Material Nom PVC - Polyvinyl Chloride 0.017					Yes			
	able Diameter								
	abic Diameter	(Norman).	. 0.105						
Electric	al Charact	eristics	5						
		eristics	5						
Electricals		eristics		ce Cond	-to-Cond	I Ma	ax. Current		
Electricals	s nductor DCR		pacitan		-to-Cond		ax. Current er Conductor at 30°C		
Electricals Nom. Col 17.6 Ohm	s nductor DCR	Nom. Ca	pacitan		-to-Cond				
Electricals Nom. Col 17.6 Ohm /oltage	s nductor DCR n/1000ft	Nom. Ca	pacitan		-to-Conc				
Electricals Nom. Co 17.6 Ohm /oltage UL Voltage	s nductor DCR	Nom. Ca	pacitan		-to-Conc				
Electricals Nom. Col 17.6 Ohm /oltage	s nductor DCR n/1000ft	Nom. Ca	pacitan		-to-Conc				
ilectricals Nom. Col 17.6 Ohm /oltage UL Voltag 300 V	s nductor DCR n/1000ft	Nom. Ca 18 pF/ft (1 pacitan (59 pF/m		-to-Conc				
Electricals Nom. Col 17.6 Ohm /oltage UL Voltag 300 V Mechan	s nductor DCR //1000ft ge Rating nical Chara	Nom. Ca 18 pF/ft (1 pacitan (59 pF/m		-to-Conc				
Electricals Nom. Co 17.6 Ohm /oltage UL Voltag 300 V Mechan	s nductor DCR 1/1000ft ge Rating hical Chara	Nom. Ca 18 pF/ft (ncteristi	1 pacitan (59 pF/m		-to-Cont				
Electricals Nom. Col 17.6 Ohm /oltage UL Voltag 300 V	s inductor DCR in/1000ft ge Rating hical Chara ure verature Op	Nom. Ca 18 pF/ft (ipacitan (59 pF/m		-to-Conc				
Electricals Nom. Co 17.6 Ohm /oltage UL Voltag 300 V Mechan Femperatu	s inductor DCR in/1000ft ge Rating hical Chara ure verature Op	Nom. Ca 18 pF/ft (ccteristi	ipacitan (59 pF/m		-to-Conc				
Electricals Nom. Co 17.6 Ohm /oltage UL Voltag 300 V Mechan Femperatu	s nductor DCR y/1000ft ge Rating hical Chara ure erature Op -20°C	Nom. Ca 18 pF/ft (ccteristi	ipacitan (59 pF/m		-to-Cont				
Electricals Nom. Co 17.6 Ohm /oltage UL Voltag 300 V /lechan 'emperatu UL Temp 75°C	s nductor DCR y/1000ft ge Rating hical Chara ure erature Op -20°C ius rry Min. Insta	Nom. Ca 18 pF/ft (acteristi perating C to +75°C	ipacitan (59 pF/m ics		-to-Cond				

36.4 lbs (16.5 kg)

Bulk Cable Weight: 15 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL1666 Riser, FT4, IEEE 1202 FT4
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6541UE

History

Update and Revision:

Revision Number: 0.294 Revision Date: 05-05-2023

Part Numbers

Variants

ltem #	Color	UPC
5541UE 0081000	Gray	612825164302
5541UE 008U1000	Gray	612825164296

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.