



Click here for the 3D model.

Dimensions	
Chip Size	0504
L	1.269mm +/-0.254mm (0.05 in +/-0.01 in)
W	1.015mm +/-0.254mm (0.04 in +/-0.01 in)
Т	1.142mm MAX (0.045 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

0.51mm +/-0.25n

Packaging Specifications

Packaging

Bulk, Bag

General Information	
Series	GR900 SMD Space
Style	SMD Chip
RoHS	Yes
Termination	Gold
Failure Rate	N/A
Testing and Reliability	Mil-PRF-123 Group A
Qualifications	MIL-PRF-123 Group A
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

Specifications				
Capacitance	1500 pF			
Capacitance Tolerance	5%			
Voltage DC	50 VDC			
Temperature Range	-55/+125°C			
Temperature Coefficient	BX			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.