

TINA-BW

~60° batwing beam. Assembly with black holder, installation tape and location pins.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16.1 mm
Height	9.5 mm
Fastening	tape, pin
ROHS compliant	yes 🕕



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
TINA-BW	Single lens	PMMA	clear	
TINA-HLD-PIN-BLK	Holder	PC	black	
TINA-TAPE3	Tape	Acrylic foam	black	

ORDERING INFORMATION:


» Box size: 470 x 240 x 105 mm

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FA16662_TINA-BW	Single lens	2016	288	144	3.4

Published: 07/05/2018 Last update: 09/05/2018 Subject to change without prior notice 1/6



PRODUCT DATASHEET FA16662_TINA-BW



See also our general installation guide: www.ledil.com/installation_guide

2/6



PHOTOMETRIC DATA (MEASURED):

CREE \$


LED XHP35 HI

FWHM / FWTM Asymmetric Efficiency 79 %

Peak intensity 0.9 cd/lm

LEDs/each optic 1

Light colour White Required components:



CREE ÷

LED XP-E2

FWHM / FWTM Asymmetric

Efficiency 77 %


Peak intensity 0.8 cd/lm

White

LEDs/each optic 1

Required components:

Light colour



DESCRIPTION LUMILEDS

LED LUXEON TX


FWHM / FWTM Asymmetric

Efficiency 77 %

Peak intensity 0.8 cd/lm

LEDs/each optic 1
Light colour White

Required components:



OSRAM

LED OSLON SSL 150

FWHM / FWTM Asymmetric


Efficiency 77 %

Peak intensity 0.9 cd/lm

LEDs/each optic 1

Light colour White

Required components:






PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LH351B $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ Asymmetric 75 % Efficiency

0.6 cd/lm Peak intensity

LEDs/each optic Light colour White Required components:




SAMSUNG

LED LH351C FWHM / FWTM Asymmetric Efficiency 78 %

Peak intensity 0.7 cd/lm LEDs/each optic 1 Light colour White

Required components:



Published: 07/05/2018




PHOTOMETRIC DATA (SIMULATED):

OSRAM Opto Semiconductors

LED SYNIOS S2222 (KW DDLM31)

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ Asymmetric Efficiency 97 % 1.1 cd/lm Peak intensity LEDs/each optic Light colour White

Required components:



Published: 07/05/2018



PRODUCT DATASHEET FA16662 TINA-BW

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

6/6

www.ledil.com/ where_to_buy