

10-32 Rack Rail Clip Nuts 1421N Series





Clip Nuts (Also known as Speed nuts or Timmerman nuts) are a great alternative to **Cage Nuts** and have many more uses. Whether your rack has non-threaded round holes or square, clip nuts are an easier solution to speed up your installation.

Features

- 10-32 clip nuts for non-threaded rack rails.
- · Heat-treated by means of austempering.
- · Available in black or plated steel finish.
- Ships in a clam shell or resealable jar, depending on quantity.

Specifications

- Constructed of SAE 1050-1065 spring steel.
- Recommended torque spec 31.4 +/- 20% inch-lbs
- For use with 0.069-0.079" panel thickness.
- Hardness: HRC 38-42.
- Maximum load rating will vary depending on rail mounting and cabinet load rating.
- 1421NP are zinc plated CR3.

Gallery















| Part No. | Part No. | Quantity | |
|--------------------|--------------------|---------------|--------------|
| Black Oxide Finish | Zinc Plated Finish | Included | Package Type |
| 1421N25 | 1421NP25 | 25 clip nuts | Clam Shell |
| 1421N100 | 1421NP100 | 100 clip nuts | Plastic Jar |
| 1421N250 | 1421NP250 | 250 clip nuts | Plastic Jar |

10-32 Mounting Screw and Clip Nut Combo-Pack

| Part No. | Qty Included | Clip Nuts | Rack Screws | Package Type |
|----------------|--------------|-----------------------|---|--------------|
| CLPKIT1032-10 | 10 of each | Zinc plated clip nuts | Black Screws with installed nylon washers | Clam Shell |
| CLPKIT1032-25 | 25 of each | Zinc plated clip nuts | Black Screws with installed nylon washers | Plastic Jar |
| CLPKIT1032-50 | 50 of each | Zinc plated clip nuts | Black Screws with installed nylon washers | Plastic Jar |
| CLPKIT1032-100 | 100 of each | Zinc plated clip nuts | Black Screws with installed nylon washers | Plastic Jar |

Tags: U-Style, Clip-On Nut, Captive Nut, Tinnerman Nuts, Speed Nut, J-Type Nut Retainers, U-Type Nut Data subject to change without notice Retainers, G-Nuts, G-Type Cage Nuts, Clip-on-cage nuts

© 2023. Hammond Manufacturing Ltd. All rights reserved.