	т Q I I I I I I I I I I I I I I I I I I				
4					
3		LAYOUT SHOWN AS EXAMPLE			
	Keying Shown as example				
	CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
2	-Shell Material : Aluminium -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer				
[-Durability : 500 Mating cycles -Delivered without Souriau contacts	PN: 8D521Z42SCL			
	-Temperature Range : -65°C to +175°C	A 12-10-2016 First Release			
	-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING			
		TITLE Aluminium Plug 8D series			
<u> </u>	BASIC SERIES: 8D 5 - 21 Z 42 S C L SHELL TYPE : Plug with RFI Shielding Delivered W/O C Delivered W/O C	SCALE General linear NPRDS / PROJECT Tolerances: 859			
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 N)				
	PLATING : Z = Black Zinc Nickel CONTACT LAYOUT	T: 21-42 FORMAT SOURIAU DRG N° SHEET			
		A3 8D521Z42SCL-C 1/2			

r	Ŧ	G	н п	m	U	0	
4		Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ယ							
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	oducts wh v either o mmendat
N						PN: 8D	Countr FR
					A 12-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
_					SCALE NA	Genera 	Alumin al linear rances:
					FORMAT	U WWW.SOUR SOU	
	Н	G	F	E	A3 D		521Z4

