

**Features**

- Designed for 10Gig Ethernet applications, OM4 Rated
- MPO/8xLC connectors
- Backward compatible with legacy optical LAN
- Maximum 10Gb distance of 300 meters at 850NM
- TPU Jacket
- 20m length
- Ideal for Fibre Channel (SAN) application
- IEEE 802.3ae and TIA LOMM compliant
- Use with VCSEL and LED laser light sources



**Product Description**

This is a 20m MPO (female) to 8xLC (male) 8-strand aqua riser-rated fiber fanout cable. An OM4 cable has a core size of 50m microns that supports 10 Gigabit Ethernet at lengths measuring up to 550 meters, and 100 Gigabit Ethernet measuring up to 150 meters and is reverse compatible with OM3. This optical fiber, nonconductive, riser (OFNR) cable is best suited for use in interior fiber-optic applications. Our patch cables are 100% compliant for all of your networking needs. Our products are guaranteed by federal law to not affect or void OEM warranties.

Applications	OM1 (MMF)		OM3 (MMF)		OM4 (MMF)		OS2 (SMF)	
	850nm	1300nm	850nm	1300nm	850nm	1310nm	1310nm	1550nm
<b>ATM 622Mbps</b>	300m	500m	300m	500m			2000m	
<b>Fiber Channel 1062Mbps</b>	300m		500m				2000m	
<b>FDDI</b>		2000m		2000m		2000m		
<b>100Base-FX Ethernet</b>		2000m		2000m		2000m		
<b>1000Base-SX Ethernet</b>	275m		550m		1000m			
<b>1000Base-LX Ethernet</b>	550m			>500m		>500m	5000m	
<b>10GBase-LX4 Ethernet</b>		300m					1000m	
<b>10GBase-SR/SW Ethernet</b>	33m		300m		550m		1000m	40000m
<b>40GBase-SR/LR Ethernet</b>			300m		400m			
<b>100GBase-SR Ethernet</b>			100m		150m			
<b>100GBase-LR Ethernet</b>							1000m	40000m

Type	Single-mode			Multimode
Polishing	PC		APC	PC
Insertion Loss	≤ 0.2dB (Typical ≤0.1dB)			≤ 0.3dB/0.5dB (MTRJ)
Return Loss (each channel)	≥ 45dB	≥55dB	≥60dB	≥ 35dB
Durability (500 matings)	≤ 0.2dB increase (Max)			
Operating Temperature	-40°C~+75°C			
Storage Temperature	-40°C~+75°C			