	CONNECTING Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ous Materia	als and Mfg Information			
Supplie	r Information														
Company	name*	Company un	Company unique ID			Unique ID Authority					Response Date*				
onsemi												2023-06-08			
Contact N	lame		Title - Contact				Phone - Contact*					Email - Contact*			
Product-l	Env-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
uthorize	ed Representative*		Title - Representative				Phone - Representative*				Email - Representative*				
Product-l	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Date	tive Date Version Manufacturing Sit		ing Site	v	/eight*	UOM	Unit Type	
	GBU6B			BR GBU4L GPPN 6A 100V			2023-06-08			TSCBE		3	995.245	mg	Each
/anufa	cturing Proccess Informat	ion										'			
	Terminal Plating / Grid Array Material		Ferminal Base Alloy J-STD-020		J-STD-020 MS	L Rating	Peak Process Body Temper		dy Temperatu	ture Max Time at Peak		Temperatu	re Numb	er of Reflow Cyc	les
	Matte Tin (Sn) - annealed		U Alloy NA			0 C		С	30		second	s 3			
omments	3														
or more	information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	15.0	mg	Supplier	Silicon (Si)	7440-21-3		15	mg
Die Attach Solder	15.025	mg	Supplier	Silver (Ag)	7440-22-4		0.3756	mg
			А	Lead (Pb)	7439-92-1	7a	13.8981	mg
			Supplier	Tin (Sn)	7440-31-5		0.7512	mg
Lead Frame	1799.6	mg	Supplier	Iron (Fe)	7439-89-6		2.6994	mg
			Supplier	Copper (Cu)	7440-50-8		1796.0009	mg
			Supplier	Phosphorus (P)	7723-14-0		0.8998	mg
Mold Compound-Black	2160.0	mg		Epoxy resin	proprietary data		108	mg
			Supplier	Phenolic Resin	Proprietary Data		162	mg
			Supplier	Carbon Black (C)	1333-86-4		10.8	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		324	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		1555.2001	mg
Plating	5.62	mg	Supplier	Tin (Sn)	7440-31-5		5.62	mg