

Specification Sheet

Part Number: 151-02051



HellermannTyton's 4x oval fir tree prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

Angled connector clip allows for clearance from obstructions and sheet metal contours.

Connector clip design meets USCAR EWCAP-005-11 clip slot specifications, assuring compliance.

Article Number 151-02051

Type CC22

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip, 6.2–13.0mm Hole Dia., PA66HIRHSUV, Black, 5000/carton

Global Part Name

CC22-PA66HIRHSUV-BK

Length L (Imperial)

1.01

Length L (Metric)

25.71

Fixation Method

Fir Tree

Width W (Imperial)

0.69

Width W (Metric)

17.53

Height H (Metric)

26.0

Panel Thickness Min (Imperial)

0.02

Panel Thickness Max (Imperial)

0.27

Panel Thickness Min (Metric)

0.51

Panel Thickness Max (Metric)

6.75

Mounting Hole Diameter D (Imperial)

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

Mounting Hole Diameter D (Metric)

7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 6.5 x 12.5 mm

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)

0.51

Mounting Hole Diameter D Max (Metric)

13.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988