


## 30HV15B822MN

Aliases (30HV15B822M)

HV RAD-LDD Indust X7R HVHT200C, Ceramic, 8200 pF, 20%, 3000 VDC, X7R, Commercial, High Temperature, HighVoltage, Lead Spacing = 15.24mm



Click here for the 3D model.

Dimensions	
L	18.29mm MAX
Н	17.78mm MAX
Т	7.62mm MAX
S	15.24mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications	
Packaging	Waffle
Packaging Quantity	20

General Information		
Series	HV RAD-LDD Indust X7R HVHT200C	
Style	Radial	
Description	Commercial, High Temperature, HighVoltage	
Features	Commercial	
RoHS	With Exemptions	
REACH	SVHC (Pb - CAS 7439-92-1)	
SCIP Number	ef26097b-3862-4ee0-b0ad-404a563ece0f	
Termination	Nickel	
Failure Rate	N/A	
AEC-Q200	No	

Specifications	
Capacitance	8200 pF
Capacitance Tolerance	20%
Voltage DC	3000 VDC
Dielectric Withstanding Voltage	4500 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	X7R
Dissipation Factor	2%
Aging Rate	2% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.