

TOLERANCE UNLESS OTHERWISE SPECIFIED					
.X	±0.25				
.XX	±0.13				
XXX	+0.05				

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, 30µ" GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 50Ω (IMPEDANCE)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



PART NUMBER:

10.	ſ		Ī

67

COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 629 COMBO ASSEMBLY				
DRAWN: C.B	DATE: JAN. 01/2019			
CHECKED:	DATE:			
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2			
DRAWING NUMBER: 629-2WK2640-5T4				

629-2WK2640-5T4

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25
.XX ±0.13

.XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2





5W1

0000 3W3







11W1

○ ○ ○ ○ ○ ○ ○ ○






13W3









17W5











21W4











COMBINATION D-SUB



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

DRAWN: C.B	DATE: JAN. 01/2019				
CHECKED:		DATE:			
SCALE: N.T.S		SHEET	2	OF	2
DRAWING NUMBER: 6	629-2WK	2640-5T4	ļ		ISSUE

629-2WK2640-5T4

629 COMBO ASSEMBLY

SW REFERENCE NO.:

PART NUMBER: