

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER						
ORIGINAL						

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

**OPERATING TEMPERATURE:** 

.X ±0.25 .XX ±0.13 .XXX ±0.05

> COPPER ALLOY, 30µ" GOLD PLATED -55°C ~ 125°C

STEEL, TIN PLATED

THERMOPLASTIC POLYESTER, UL94V-0


POWER/CO-AX CONTACT RATING:

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.


**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:

5000MΩ min.

1000V AC rms



				SW REFERENCE NO.: 629 COMBO ASSEMBLY					
	COMBINATION D-SUB				DRAWN: C.B		DATE: JAN. 01/2019		
				CHECKED:		DATE:			
		EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND	SCALE: (IN C.A.I	D. 1:1)	SHEET	1	OF	2
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-3W3-640-3T5				ISSUE		
YOUF	R CONNECTION TO	TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER:	629-3W3	-640-3T5			1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. 30A (CURRENT)

