	ſ	T G T	m	D		0		Ξ	A		_
CHARACTERISTIC         Standard; Based on NUL-DTL-38999 Series II         Schell Material       A luminium         Schell Material       E lassed on NUL-DTL-38999 Series II         Schell Mattrial       E lassed on NUL-DTL-38999 Series II         Schell Partie       E lassed on NUL-DTL-38999 Series II         Oursell Parties II       Image: Schell Parties II         Oursell Partie       Schell Material         Basic Series:       Boll 7         Schell Partie       Schell Parties II         Mas       E lassed on Nul-DEC         Material       Contract Tree: Jon mut Receptacle       Schell Partie		22.6 Max W	S C C C C C C C C C C C C C C C C C C C				YOUT SHOWN AS EXAM	PLE			4
Shell Material       : Aluminum         Shell Material       : BakZine Nickel         Insulator       : Thermoplastic         -Contacts       : Copper Alloy         VTHREAD       M15x1-6g         Soul RAU shall not be liable for any non conformity or damage       uto to a set the Products which does not comply with the specifications issued by either of the Partitic or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendations acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List or by at third party (professional recommendation acontrol List o		CHARACTERISTICS	Connector dimension Dim Nominal								
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 21.05 g ± 10% BASIC SERIES: 80 7 - 11 Z 04 S A EXAMPLE STREE SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact SHELL STZE : 11 PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel 		-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1			due to a use the Specifications	of the Products which of issued by either of the onal recommendation,	does not comply v Parties or by a th technical notice.) Jurisdiction	with hird party & Control List		0
-Salt Spray       : 500 hours         -Mass       : 21.05 g ± 10%         BASIC SERIES:       8D       7       - 11       Z       04       5       A         SHELL TYPE       : Jam nut Receptacle       SCALL       General linear       NPRDS / PROJECT         CONTACT TYPE       : Standard Crimp Contact       859       ±       This document is the property of SURIAU         SHELL SIZE       : I1       CONTACT TYPE : SockET(500 Matings)       CONTACT TYPE : SOCKET(500 Matings)       SOURIAU       WWW.SOURIAU.COM       This document is the property of SURIAU         PLATING       : Z       Black Zinc Nickel       CONTACT TYPE : SOCKET(500 Matings)       FORMAT       SOURIAU DRG N°       SHEET         A3       8D711204SA-C       1/2		-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				F					2
TITLE       Aluminium Receptacle 8D series         BASIC SERIES:       8D       7       1       TITLE       Aluminium Receptacle 8D series         SASIC SERIES:       8D       7       1       Contact TYPE : Jam nut Receptacle         SASIC SERIES:       8D       7       1       Contact TYPE : Standard Crimp Contact:       NA       CONTACT TYPE : Standard Crimp Contact:       SCALE       NA       SOURIAU .COM       Souriau       This document is the property of SOURIAU         SHELL SIZE : 11       CONTACT TYPE : SOCKET(500 Matings)       CONTACT TYPE : SOCKET(500 Matings)       CONTACT LAYOUT : 11-04       SOURIAU       SOURIAU .COM       SHEET       Communicated without permission       Communicated without permission       Communicated without permission       SHEET       A3       8D711Z04SA-C       1/2       1/2       1/2		-Salt Spray : 500 hours					on - by			MOD N°	
BASIC SERIES.       SUP 7       11       2       04       3       A       Tolerances:       1         SHELL TYPE : Jam nut Receptacle       ORIENTATION : A       NA       Stell Size : 11       This document is the property of SOURIAU       SOURIAU       SOURIAU       SOURIAU       it must not be reproduced or communicated without permission         PLATING :       Z       Black Zinc Nickel       CONTACT TYPE : SOCKET(500 Matings)       FORMAT       SOURIAU DRG N°       SHEET         A3       8D711Z04SA-C       1/2				De		Date:	Aluminium Re				
A3 SOURIAO DRG N 1/2	<b>_</b>	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	ORIENTA	ATION : A	NA	J www	Tolerances: ±	M	859 This document is the pro SOURIAU it must not be reprodu	ced or	1
				51.11-04		C		SA-C	Δ		

Г	D I	ш п			
4	Contact Layout $ \begin{array}{c}  & & & \\  & & \\$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		4
	$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$		Dim Nomin	al	
ω			B 19.59+0/- ØC 20.96+0.2		3
			due to a use of the P the Specifications issued	able for any non-conformity or damage roducts which does not comply with by either of the Parties or by a third party ommendation, technical notice.)	
N			A 01-10-2016 First Release	BD711Z04SA	2
			ISS DATE Latest modification - by	N	/OD N°
			Designed By: Date: TITLE Alu	CUSTOMER DRAWING	
-				eral linear     NPRDS / PROJECT       erances:     859       ±     This document is the property       SOURIAU     SOURIAU	
			SOURIAU WWW.SOU	communicated without permiss	sion
		1		JRIAU DRG N° 0711Z04SA-C	SHEET 2/2
L	H G	FEE		B A	]