ſ	Ŧ	Q	П	m	D		O
4	R 22.6 Max	N Thread					L.
			Keying Shown as	example			
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 -Shell Material : Stainless St -Shell Plating : Passivated -Insulator : Thermopla -Contacts : Copper Allo -Seals & Grommet : Silicon Elas	eel stic by		Connector limension Dim Nominal A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g			SOURIAU sha due to a u the Specificatio (profes
N)	-Contact Plating: Gold over of-Durability: 500 Mating-Delivered with Souriau contacts and-Temperature Range: -65°C to +2-Salt Spray: 500 hours	Accessories	um			A 28-09-2016 SS DATE esigned By:	First Release Latest modifica Dat
_ _	BASIC SERIES: SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp C SHELL SIZE : 13	8D 7 - 13 Contact	K 08 S B	CONTACT TYPE : SOCKET(5	00 Matings)	TITLE SCALE NA SOURIAU	- → wwv
	PLATING : K = Passivated			CONTACT LAY	OUT : 13-08	A3	

G F

Н

С

 $\mathbf{\mathbf{n}}$

D

Е

	σ		А			
					4	
LAYOUT SHOWN AS EXA	MPLE				3	
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713K08SB						
ation - by MOD N° te: CUSTOMER DRAWING						
Stainless Steel Receptacle 8D series General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of SOURIAU SOURIAU					1	
W.SOURIAU.COM it must not be reproduced communicated without perr SOURIAU DRG N° 8D713K08SB-C B A						

ſ	Т	D	г	Ш	D	0	Ξ	A	
4	-×,	Contact Layout $G \oplus G^{H} \oplus $				Panel cutout JAM NUT RECEPTACLE (TYPE 7)			4
	Cont positi ID A B C C D E F G G H	X-axis (mm) Y-axis (mm) +.065 (1.65) +.157 (3.99) +.170 (4.32) +.000 (0.00) +.120 (3.05) 120 (3.05) .000 (0.00) 170 (4.32) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 170 (4.32) +.000 (0.00) 065 (1.65) +.157 (3.99)					γ		
ω	size no. con	Iber of Size Service Contact Supersedes tacts contacts rating location 8 8 20 I All MS20051-8				Dim Nominal B 24.26+0/-0.2 ØC 25.65+0.25/			3
						SOURIAU shall not be liabl due to a use of the Proo the Specifications issued by (professional recom	ducts which does not co	mply with y a third party	
N						PN: 8D	Country Jurisd FR 713K08SB	iction & Control List Not Listed	2
					A 28-09-2016 ISS DATE Designed By: TITLE	First Release Latest modification - by Date: Stainle	ess Steel Recepta	CUSTOMER DRAWING	<u>N°</u>
_					SCALE NA SOURIAU	Genera Tolera ±-	l linear inces: 	NPRDS / PROJECT 859 This document is the property of SOURIAU	1
	Н	G	F	E	FORMAT A3 D	SOUI	RIAU DRG N° 713K08SB-C B	it must not be reproduced or communicated without permission SHEE 2/2 A	