


ACR05D221KGS

ACR Indust COG HT200C, Ceramic, 220 pF, 10%, 100 VDC, COG, Commercial, High Temperature, Lead Spacing = 5.08mm



Dimensions		
L	5.08mm MAX	
W	5.08mm MAX	
Т	2.54mm MAX	
S	5.08mm +/-0.38mm	
LL	3.175mm MIN	
F	0.508mm +/-0.051mm	
G	4mm +0.5/-0.5mm	

Packaging Specifications				
Packaging	Bulk, Bag			
Packaging Quantity	1			

General Information	1
Series	ACR Indust COG HT200C
Style	Radial
Description	Commercial, High Temperature
Features	Commercial
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	f2ec9c71-d741-45f9-8d01-f6de6baf235a
Termination	Gold
Failure Rate	N/A
Testing and Reliability	Standard
AEC-Q200	No

Specifications				
Capacitance	220 pF			
Capacitance Tolerance	10%			
Voltage DC	100 VDC			
Dielectric Withstanding Voltage	250 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15% 1 kHz 1.0Vrms			
Insulation Resistance	100 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.