ASSOCIATION CONNECTING ELECTRONICS (MOUSTRIES + international and Pan-American c	ourn, Illinois. All rights	s reserved under both	This docume level parts, t	ent is a declarati he declaration e	on of the substan ncompasses all lo	ces within the manufactur wer level materials for w	rer listed item. which the manu	Note: if the facturer has	e item is an ass s engineering r	embly with lower esponsibility.	
IPC Web Site for Information on http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribut			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				als and Mfg Information			
Supplier Information											
ompany name* Company unique ID			1	Unique ID Authority			Response Date*				
onsemi								2023-06-08			
Contact Name	Title - Contact]	Phone - Contact*			Email - Contact*				
Product-Env-Stewards	Product Enviro Compliance			NA			Product-Env-Stewards@onsemi.com				
Authorized Representative*	Representative* Title - Representative		Phone - Representative*			Email - Representative*					
Product-Env-Stewards Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iten	n Number Mfr Ite	Mfr Item Name		Effective Date	Version	Manufacturing Site	Wei	ght*	UOM	Unit Type	
NCV87.	5SQ30T2G 50 mA Low D	A Ultra-Low Iq, Wide Inpu Dropout Linear Voltage Re	ıt Voltage, egulator	2023-06-08		MY1	6.2		mg	Each	
Manufacturing Proccess Information											
Terminal Plating / Grid Array Material	Terminal Base Alloy J-ST		SL Rating	Peak Process Body Temperature		ature Max Time at Peak	K Temperature Numb		of Reflow Cycl	es	
Matte Tin (Sn) - annealed CU Alloy 1				260	С	30	seconds	3			
Comments											
evel 1 - maximum time at peak temperature during so	ldering is 10-30 second	nds									
For more information regarding material composition	please refer to page 3	3									

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).								
Homogeneous Material	Weight Unit of Measure Level Substance		CAS	Exempt	Weight	Unit of Measure		
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg
Die Attach	0.12	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.078	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.042	mg
Lead Frame	1.92	mg	Supplier	Silver (Ag)	7440-22-4		0.0384	mg
			В	Nickel (Ni)	7440-02-0		0.697	mg
			Supplier	Iron (Fe)	7439-89-6		0.9638	mg
			Supplier	Copper (Cu)	7440-50-8		0.2208	mg
Mold Compound-Black	3.9	mg		Epoxy resin	proprietary data		0.195	mg
			Supplier	Phenolic Resin	Proprietary Data		0.195	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.078	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0195	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.4125	mg
Plating	0.05	mg	Supplier	Tin (Sn)	7440-31-5		0.05	mg
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).