



PRODUCT SPECIFICATION

TITLE

ISM 433MHz Flex Antenna

TABLE OF CONTENTS

- 1.0 SCOPE
- 2.0 PRODUCT DESCRIPTION
- 3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS
- 4.0 RATINGS
- 5.0 PERFORMANCE
- 6.0 TEST GROUPINGS
- 7.0 PACKING

REVISION: A1	ECR/ECN INFORMATION: EC No: 122214 DATE: 2017-08-11	TITLE: ISM 433MHz Flex Antenna	SHEET No. 1 of 7
DOCUMENT NUMBER: PS-2042870100	CREATED / REVISED BY: Colin. Xu 2017-08-09	CHECKED BY: Stary.Song 2017-08-10	APPROVED BY: Welson Tan 2017-08-11



PRODUCT SPECIFICATION

ISM 433MHz Flex Antenna

1.0 SCOPE

This Product Specification covers the mechanical, electrical and environmental performances requirements and test methods for ISM 433MHz Flex Antenna with solder cable.

2.0 PRODUCT DESCRIPTION

2.1 PRODUCT NAME AND SERIES NUMBER (S)

Product name: ISM 433MHz Flex Antenna -2042870100

2.2 Design and Construction

Antenna construction and physical dimensions specified on the applicable sales drawing.

2.3 Materials

- a) Flex: Refer to sales drawing of 2042870100
- b) Cable Line: Refer to sales drawing of 2042870100
- c) Connector : Refer to sales drawing of 2042870100

3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS

See drawings and other sections of this specification for the relevant reference documents. In cases where the specification differs from the drawings, the drawings take precedence.

4.0 RATINGS

4.1 RF POWER

2 WATTS MAX

4.2 TEMPERATURE

Operating: - 30°C to 85°C
 Storage : - 40°C to 95°C

4.3 HUMIDITY

Operating: -30°C to 85°C
 -30°C to 50°C, 85%RH or less
 50°C to 85°C, 60%RH or less

Storage : -40°C to 95°C
 -40°C to 50°C, 85%RH or less
 50°C to 95°C, 60%RH or less

REVISION: A1	ECR/ECN INFORMATION: EC No: 122214 DATE: 2017-08-11	TITLE: ISM 433MHz Flex Antenna	SHEET No. 2 of 7
DOCUMENT NUMBER: PS-2042870100	CREATED / REVISED BY: Colin. Xu 2017-08-09	CHECKED BY: Stary.Song 2017-08-10	APPROVED BY: Welson Tan2017-08-11



PRODUCT SPECIFICATION

5.0 PERFORMANCE

5.1 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 50mm(2042870050)

DESCRIPTION	TEST CONDITION	REQUIREMENTS
Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.8dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>56%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

5.2 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 100mm (2042870100)

Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.7dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>55%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

REVISION: A1	ECR/ECN INFORMATION: EC No: 122214 DATE: 2017-08-11	TITLE: ISM 433MHz Flex Antenna	SHEET No. 3 of 7
DOCUMENT NUMBER: PS-2042870100	CREATED / REVISED BY: Colin. Xu 2017-08-09	CHECKED BY: Stary.Song 2017-08-10	APPROVED BY: Welson Tan2017-08-11



PRODUCT SPECIFICATION

5.3 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 150mm (2042870150)

DESCRIPTION	TEST CONDITION	REQUIREMENTS
Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.6dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>54%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

5.4 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 200mm (2042870200)

DESCRIPTION	TEST CONDITION	REQUIREMENTS
Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.5dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>52%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

REVISION:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
A1	EC No: 122214 DATE: 2017-08-11	ISM 433MHz Flex Antenna	4 of 7
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
PS-2042870100	Colin. Xu 2017-08-09	Stary.Song 2017-08-10	Welson Tan 2017-08-11



PRODUCT SPECIFICATION

5.5 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 250mm (2042870250)

Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.4dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>51%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

5.6 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 300mm (2042870300)

DESCRIPTION	TEST CONDITION	REQUIREMENTS
Description	Test Condition	Requirements
Frequency Range	Measure antenna on recommended PCB through VNA E5071C	433MHz+/-3MHz
Return Loss	Measure antenna on recommended PCB through VNA E5071C	< -10 dB
Peak Gain (Max)	Measure antenna on recommended PCB through OTA chamber	0.3dBi
Avg. Total Efficiency	Measure antenna on recommended PCB through OTA chamber	>50%
Polarization	Measure antenna on recommended PCB through OTA chamber	Linear
Input Impedance	Measure antenna on recommended PCB through VNA E5071C	50 Ohms

REVISION: A1	ECR/ECN INFORMATION: EC No: 122214 DATE: 2017-08-11	TITLE: ISM 433MHz Flex Antenna	SHEET No. 5 of 7
DOCUMENT NUMBER: PS-2042870100	CREATED / REVISED BY: Colin. Xu 2017-08-09	CHECKED BY: Stary.Song 2017-08-10	APPROVED BY: Welson Tan2017-08-11



PRODUCT SPECIFICATION

5.7 CABLE LOSS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.7.1	Frequency Range	433MHz	433MHz
5.7.2	Attenuation	1m cable measured by VNA5071C	≤1dB/m

5.8 CABLE LENGTH AFFECT THE ANTENNA PERFORMANCE

Balance antenna resonance is insensitive by cable's length, but the cable's loss will affect the total Efficiency. Refer to 5.7

5.9 MECHANICAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.9.1	Pull test	Test machine : Max intelligent load tester Stick the flex antenna in a PC block, pull cable in horizontal direction	Pull force >8 N

5.10 ENVIRONMENTAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.10.1	Temperature /Humidity cycling	Test condition: 1) The device under test is kept for 30 mins in an environment with a temperature of -40 °C. 2) Kept for 4 Hours in an environment with a temperature of 85 degrees and a relative humidity of 95%. 3) Kept for 2 Hours in an environment with a temperature of 125 degrees and a relative humidity of 95%. 4) The cycle is repeated until a total of 40 cycles have been completed. Hereafter the conditions are stabilized at room temperature.	1) Parts should meet RF spec before and after test. 2) No cosmetic problem
5.10.2	Temperature Shock	Test condition: The device under test at -40 °C ⇔ 125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle) and each item should be measured after exposing them in normal temperature and humidity for 24 h.	1) Parts should meet RF spec before and after test. 2) No cosmetic problem

REVISION:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
A1	EC No: 122214 DATE: 2017-08-11	ISM 433MHz Flex Antenna	6 of 7
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
PS-2042870100	Colin. Xu 2017-08-09	Stary.Song 2017-08-10	Welson Tan 2017-08-11



PRODUCT SPECIFICATION

5.10.3	High Temperature	Test condition: 1) Temperature:125°C, time:1008hours 2) There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other	1) Parts should meet RF spec before and after test. 2) No cosmetic problem
5.10.4	Salt mist test	1. Test condition: The device under test is exposed to a spray of a 5% (by volume) resolution of NaCL in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature.	1) Parts should meet RF spec before and after test. 2) No visible corrosion, discoloration accept.

The meaning of text “**No Cosmetic Problem**” in the table above is:

- a. No soldering problem
- b. No adhesion problem of glue
- c. Cable & connector assembly orientation rotates 20°Max

6.0 TEST GROUPINGS

Test Item	Description	Group1	Group2	Group3	Group4	Group5
5.9.1	Pull test	X				
5.10.1	Temperature /Humidity cycling		X			
5.10.2	Temperature Shock			X		
5.10.3	High Temperature				X	
5.10.4	Salt mist test					X
Sample Quantity		5	5	5	5	5

7.0 PACKAGING

Refer to Molex packaging drawing of 2042870100

REVISION: A1	ECR/ECN INFORMATION: EC No: 122214 DATE: 2017-08-11	TITLE: <h3 style="text-align: center;">ISM 433MHz Flex Antenna</h3>	SHEET No. <h3 style="text-align: center;">7 of 7</h3>	
DOCUMENT NUMBER: <h3 style="text-align: center;">PS-2042870100</h3>		CREATED / REVISED BY: Colin. Xu 2017-08-09	CHECKED BY: Stary.Song 2017-08-10	APPROVED BY: Welson Tan2017-08-11