	I	Q	п	т	D	0
4	R 22.6 Max	N Thread				
			Keying Shown as	example		
N	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 -Shell Material : Stainless Str -Shell Plating : Nickel -Insulator : Thermoplas -Contacts : Copper Allor -Seals & Grommet : Silicon Elast -Contact Plating : Gold over co -Durability : 500 Mating -Delivered with Souriau contacts and	eel stic y tomer opper Alloy 0.8µm minimum cycles		Connector dimension           Dim         Nominal           A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g		SOURIAU shall due to a use the Specification (profess
	-Temperature Range <u>:</u> -65°C to +2 -Salt Spray : 500 hours				ISS DA Designed By:	Date
-	BASIC SERIES: SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Co SHELL SIZE : 13		S 03 P B	ORIE CONTACT TYPE : PIN(5	SCALE NA NTATION : B SOURI	
	PLATING : S = Nickel			CONTACT TYPE : PIN(5 CONTACT LAY	/OUT : 13-03	
			•		A3	
	н	G	F	E	D	С

D		A				
				4		
LAYOUT SHOWN AS EXAMPLE				3		
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713S03PB						
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series						
General linear     NPRDS / PROJECT       Tolerances:     859       ±     This document is the property of				1		
W.SOURIAU.COM	ed or rmission SHEET					
8D713S03PB	-C	A	1/2			

Contact layout $ \begin{array}{c} 03 \\ \hline 0 \\ \hline \hline 0 \\ \hline 0 \\ \hline \hline \hline \hline 0 \\ \hline \hline \hline \hline \hline 0 \\ \hline \hline$	4
Ctc       X       Y         A       2.39       1.47         B       0       -2.79         C       -2.39       1.47         Dim       Nominal B         Dim       24.26+0/-0.25	
	3
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	2
A       28-09-2016       First Release       ISS       DATE       Latest modification - by       MOD         Designed By:       Date:       CUSTOMER DRAWING       MOD	°
TITLE     Stainless Steel Receptacle 8D series       SCALE     SCALE       NA     General linear       Tolerances:     859       ±     This document is the property of	1
H       G       F       E       D       C       B       A	