

### **Mounting Option**

12-.128 (3.25) Dia. Side Mounting Holes

#### **Contact Detail**

523-P.C. Tail .025 Sq.(0.64 Sq.) - Tail LG=.390(9.91) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing






## **See Accompanying Page for:**

- **Bend Detail**
- **Mounting Options**
- **Features and Specifications**





| 333 Series Card Edge Connector   |                             |                                   | ACAD REFERENCE NO. 333 ENG MASTER |         |           |        |
|--|-----------------------------|-----------------------------------|-----------------------------------|---------|-----------|--------|
| Part Number: 333-008-523-112   |                             | DRAWN:                            | J.LEE                             | DATE: O | CT. 14/09 |        |
|  |                             | CHECKED:                          |                                   | DATE:   |           |        |
|  | EDAC INC                    | THESE DRAWINGS AND SPECIFICATIONS | SCALE:                            | NTS     | SHEET     | 1 OF 4 |
| TORONTO, ONTARIO  ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE |                             | DRAWING                           | NUMBER                            |         | ISSUE     |        |
| OUR CONNECTION TO  | CANADA<br>QUALITY & SERVICE | MANUFACTURE OR SALE OF APPARATUS  | 333 Assembly                      |         |           | 1      |

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

1



| 333 Series Card Edge Connector<br>Contact Bend Detail                                 |                                   | ACAD REFERENCE NO. 333 ENG MASTER |                  |        |  |
|---|-----------------------------------|-----------------------------------|------------------|--------|--|
|   |                                   | DRAWN: J.LEE                      | DATE: OCT. 14/09 |        |  |
|   |                                   | CHECKED:                          | DATE:            |        |  |
| EDAC INC  | THESE DRAWINGS AND SPECIFICATIONS | SCALE: NTS                        | SHEET :          | 2 OF 4 |  |
| TORONTO, ONTARIO ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIE | DRAWING NUMBER                    |                                   | ISSUE            |        |  |
| YOUR CONNECTION TO QUALITY & SERVICE  | MANUFACTURE OR SALE OF APPARATUS  | 333 Assembly                      |                  | 1      |  |

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER



1220F NOWRE

DRIGINAL

1



|                  | 333 Series Card Edge Connector  |                                   | ACAD REFERENCE NO. 333 ENG MASTER |             |           |        |
|------------------|---|-----------------------------------|-----------------------------------|-------------|-----------|--------|
| Mounting Options |   | DRAWN:                            | J.LEE                             | DATE: O     | CT. 14/09 |        |
|                  | Moorning Ophons   |                                   | CHECKED:                          |             | DATE:     |        |
|                  | COOO EDAC INC   | THESE DRAWINGS AND SPECIFICATIONS | SCALE:                            | NTS         | SHEET ;   | 3 OF 4 |
|                  | TORONTO, ONTARIO ARE THE PROPERTY OF EDAG INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE | DRAWING                           | NUMBER                            |             | ISSUE     |        |
|                  | CANADA OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.                    |                                   | 3                                 | 33 Assembly |           | 1      |

ISSUE NUMBER

ORIGINAL



## **Features**

- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- High Profile Insulator Body .600 (15.24)
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree, & Extender Board Bends
- Single or Dual Row Configurations
- Variety of Mounting Options, Flush or Offset Lugs
- Accepts Between Contact and In-Contact Polarizing Keys

# **Specifications**

- Insulator Material: Thermoplastic Polyester, UL 94V-0, Colour: Green
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 3 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +105 Degrees C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 333 Series Card Edge Connector                           | ACAD REFERENCE NO. 333 ENG MASTER      |
|--|--|
| Features and Specifications                              | DRAWN: J.LEE DATE: OCT. 14/09          |
| redictes and specifications                              | CHECKED: DATE:                         |
| EDAC INC THESE DRAWINGS AND                              |  |
|  | DDUCED, OR COPIED DRAWING NUMBER ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE WITHOUT WRITTEN PER | LE OF APPARATUS 333 Accombly 1         |