

## Specification Sheet

Part Number: 556-04037



Prints detectable TipTag markers, as well as thermal transfer labels and more, for use in food, beverage and pharmaceutical operations. High-volume, ultra-fast, premium-quality printing for dependable performance and excellent results.

Color LCD touchscreen for intuitive control.

Optional premium quality accessories such as a perforator and cutter extend the printer's capability.

TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg

<b>Article Number</b>	556-04037
-----------------------	-----------

<b>Type</b>	TT4030
-------------	--------

<b>Color</b>	Gray (GY)
--------------	-----------

<b>Quantity Per</b>	EA
---------------------	----

<b>Product Description</b>	HellermannTyton's TT4030 Series thermal transfer printers are designed for high-volume, industrial-grade printing of thermal transfer labels and ShrinkTrak. Their user-friendly design features an informative display for simple navigation and instructional videos. The built-in caddy allows even the largest label rolls to fit inside, and the cutter can cut through the thickest material. The TT4030's print head delivers excellent results. This printer handles all sizes of HellermannTyton's ShrinkTrak markers and can print on even the smallest labels. Use with HellermannTyton's TagPrint Pro label printing software.
<b>Short Description</b>	TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg
<b>Global Part Name</b>	TT4030-MET-GY
<b>Length L (Imperial)</b>	15.0
<b>Length L (Metric)</b>	381.0
<b>Width W (Imperial)</b>	9.21
<b>Width W (Metric)</b>	252
<b>Height H (Imperial)</b>	11.34
<b>Height H (Metric)</b>	288
<b>Depth D (Imperial)</b>	18.11
<b>Depth D (Metric)</b>	460
<b>Power Supply</b>	100-240V / 50-60Hz

<b>Material</b>	Metal (MET)
<b>Material Shortcut</b>	MET
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	+40°F to +104°F (+4°C to +40°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	iLab   EN 61000-6-2 iLab   DIN EN 55032:2012-12 iLab   DIN EN 55032 rectification 1:2013-04 CE   2011/65/EU iLab   IEC 60950-1 (ed.2), am2 iLab   DIN EN 61000-6-2:2006-03 CE   2014/35/EU iLab   EN 61000-3-2 iLab   CE 2014/35/EU iLab   IEC 60950-1 (ed.2), am1 iLab   IEC 60950-1 (ed.2) iLab   DIN EN 61000-6-2 rectification 1:2011-06 iLab   DIN EN 55032:2016-02
<b>Package Quantity (Imperial)</b>	1
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	8443913000