

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING: 40A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


INSULATOR RESISTANCE: DIELECTRIC

WITHSTANDING VOLTAGE:

5000MΩ min.

-55°C ~ 125°C

1000V AC rms



ISSUE NUMBER

(1)

	COMBINATION D-SUB			SW REFERENCE NO.: 630 COMBO ASSEMBLY		
				DATE: JAN. 01/20	19	
		CHECKED:	DATE:			
	EDAC INC TORONTO, ONTARIO CANADA) QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
			DRAWING NUMBER: 630-17W5250-4T6		ISSUE	
YOUR CONNECTION TO			PART NUMBER: 630-17W	5250-4T6	1	



12.50

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

