

ignion<sup>™</sup>

Your innovation.  
Accelerated.

# RUN mXTEND<sup>™</sup> (NN02-224)

DATASHEET

## RUN mXTEND<sup>™</sup> (NN02-224)

The RUN mXTEND<sup>™</sup> cellular embedded **IoT antenna** is an example of the new generation of tiny antenna boosters available for multiband connectivity. The miniature antenna booster is connected to the RF transceiver through a matching network that shapes the frequency response of the wireless platform such as **2G, 3G, 4G** bands, but also for other regions of the spectrum for example **GNSS and Bluetooth**.



### Product Benefits

- **Top performance:** Top multiband IoT performance in a ultracompact form factor: 12.0 mm x 3.0 mm x 2.4 mm.
- **Multiband & Multiport:** 2G/3G/4G/5G, LTE-M and NB-IoT applications
- **Global reach:** Through multiband performance (compatible with multiple regional standards).
- **Reliability:** Off-the-Shelf standard product, no antenna part customization (electronic optimization).
- **Use cases:** Small tracking devices, IoT sensors and IoT cellular/ISM modules, mobile devices.

### Operation Bands Summary

- GSM, UMTS, 4G, GNSS, Bluetooth, Wi-Fi Dual Band (824 – 960MHz, 1710 – 2690MHz, 1561 – 1606MHz, 2400 – 2500MHz and 4900 – 5875MHz)

## 1. AVAILABLE SOLUTIONS SUMMARY

Class	Frequency Regions	Frequency range	More detailed info
1 Port	2	824 – 960 MHz & 1710 – 2690 MHz	<b><u>CELLULAR LTE</u></b>
1 Port	1	863 – 928 MHz	<b><u>ISM</u></b>
1 Port	3	1561 MHz, 1575 MHz & 1598 – 1606 MHz	<b><u>GNSS</u></b>
1 Port	1	2400 – 2500MHz	<b><u>BLUETOOTH</u></b>
1 Port	2	2400 – 2500MHz & 4900 – 5875MHz	<b><u>Wi-Fi DUAL BAND</u></b>

## 2. DETAILED AVAILABLE SOLUTIONS

### 2.1. LTE SOLUTION

Technical features	824 – 960 MHz	1710 – 2690 MHz
Average Efficiency	> 65 %	> 70 %
Peak Gain	1.8 dBi	1.9 dBi
VSWR	< 3:1	
Radiation Pattern	Omnidirectional	
Polarization	Linear	
Weight (approx.)	0.19 g	
Temperature	-40 to + 125 °C	
Impedance	50 Ω	
Dimensions (L x W x H)	12.0 mm x 3.0 mm x 2.4 mm	

Technical features. Measures from the evaluation board (131 mm x 60 mm x 1 mm).

## 2.2 ISM SOLUTION

Technical features	863 – 870 MHz	902 – 928 MHz	863 – 928 MHz
Average Efficiency	> 85 %	> 85 %	> 85 %
Peak Gain	2.1 dBi	2.1 dBi	2.2 dBi
VSWR	< 2:1	< 2:1	< 2:1
Radiation Pattern	Omnidirectional		
Polarization	Linear		
Weight (approx.)	0.19 g		
Temperature	-40 to +125 °C		
Impedance	50 Ω		
Dimensions (L x W x H)	12.0 mm x 3.0 mm x 2.4 mm		

Technical features. Measures from the evaluation board with UFL cables (131 mm x 60 mm x 1 mm).

## 2.3 GNSS SOLUTION

Technical features	1561 MHz	1575 MHz	1598 – 1606 MHz
Average Efficiency	> 75 %	> 75 %	> 80 %
Peak Gain	2.9 dBi	3.0 dBi	3.3 dBi
VSWR	< 1.5:1		
Radiation Pattern	Omnidirectional		
Polarization	Linear		
Weight (approx.)	0.19 g		
Temperature	-40 to +125 °C		
Impedance	50 Ω		
Dimensions (L x W x H)	12.0 mm x 3.0 mm x 2.4 mm		

Technical features. Measures from the evaluation board with UFL cables (126.5 mm x 60 mm x 1 mm).

## 2.4 BLUETOOTH SOLUTION

Technical features	2400 – 2500MHz
Average Efficiency	> 75%
Peak Gain	4.2 dBi
VSWR	< 1.5:1
Radiation Pattern	Omnidirectional
Polarization	Linear
Weight (approx.)	0.19 g
Temperature	-40 to +125 °C
Impedance	50 Ω
Dimensions (L x W x H)	12.0 mm x 3.0 mm x 2.4 mm

Technical features. Measures from the evaluation board with UFL cables (126.5 mm x 60 mm x 1 mm).

## 2.5 Wi-Fi-DUAL BAND SOLUTION

Technical features	2400 – 2500 MHz	4900 – 5875 MHz
Average Efficiency	> 70 %	> 70 %
Peak Gain	2.9 dBi	3.1 dBi
VSWR	< 2.5:1	
Radiation Pattern	Omnidirectional	
Polarization	Linear	
Weight (approx.)	0.19 g	
Temperature	-40 to + 125 °C	
Impedance	50 Ω	
Dimensions (L x W x H)	12.0 mm x 3.0 mm x 2.4 mm	

Technical features. Measures from the evaluation board with a coplanar grounded transmission line (126.5 mm x 60 mm x 1 mm).

If you need assistance to design your matching network, please contact [support@ignion.io](mailto:support@ignion.io)

You can also try our free of charge<sup>1</sup> **NN Wireless Fast Track service** you will receive a tailored antenna design approach for free in 24h<sup>1</sup>. discover the feasibility of your next wireless project including the antenna!

<sup>1</sup> See terms and conditions for a free NN Wireless Fast-Track service in 24h at: <https://www.ignion.io/fast-track-project/>

ignion<sup>™</sup>

Your innovation.  
Accelerated.

Contact:  
[support@ignion.io](mailto:support@ignion.io)  
+34 935 660 710

#### Barcelona

Av. Alcalde Barnils, 64-68 Modul C, 3a pl.  
Sant Cugat del Vallés  
08174 Barcelona  
Spain

#### Shanghai

Shanghai Bund Centre  
18/F Bund Centre, 222 Yan'an Road East,  
Huangpu District  
Shanghai, 200002  
China

#### New Dehli

New Delhi, Red Fort Capital Parsvnath Towers  
Bhai Veer Singh Marg, Gole Market,  
New Delhi, 110001  
India

#### Tampa

8875 Hidden River Parkway  
Suite 300  
Tampa, FL 33637  
USA