

Specification Sheet

Part Number: 596-00904

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

⚠ DANGER	
Arc Flash Hazard Appropriate PPE Required	
<small>Do not operate controls or open covers without appropriate personal protection equipment.</small>	
<small>Failure to comply may result in injury or death!</small>	
<small>Refer to NFPA 70E for minimum PPE requirements.</small>	<small>HellermannTyton 596-00904</small>

Article Number 596-00904

Type AF5X35D

Color Red (RD)

Quantity Per pack

Product Description	HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.
Short Description	Arc Flash Label, DANGER APPROPRIATE PPE REQUIRED, 5.0" x 3.75", PET, Red/White, 10/pkg
Global Part Name	AF5X35D-840/281-RD
Technical Description	Arc Flash Label, Danger- Appropriate PPE required, 5.0" X 3.75", Red/White
Width W (Imperial)	5.00
Width W (Metric)	127
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	3.75
Height H (Metric)	95.25

Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen Free	Yes
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2017 NEC2011 NEC2020 NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Labels per Column	1
Labels per Row	1

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)