


THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.











NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED

40A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.


.X ±0.25 .XX ±0.13 .XXX ±0.05

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:

5000MΩ min.

1000V AC rms



| | COMBINATION D-SUB | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|--|--|-------------------------|--------------------------------------|-------|--|
| COMBIN | | | DATE: JAN. 01/20 | 19 | |
| | | | DATE: | | |
| EDAC INC TORONTO, ONTARIO CANADA | C THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | ITARIOSHALL NOT BE REPRODUCED, OR COPIEDOR USED AS THE BASIS FOR THE | DRAWING NUMBER: 629-3WK | 3650-4T3 | ISSUE | |
| YOUR CONNECTION TO QUALITY & SE | RVICE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | PART NUMBER: 629-3WK | 3650-4T3 | 1 | |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. THERMOPLASTIC POLYESTER, UL94V-0 -55°C ~ 125°C

