ſ	т		G	П	п		D	0	
4	a termination of the second se	R .6 Max	W Thread		S	ØA		<image/>	
	Keying Shown as example								
N	-Shell Plating:-Insulator:-Contacts:-Seals & Grommet:-Contact Plating:	Stainless Steel Nickel Thermoplastic Copper Alloy Silicon Elastomer Gold over copper 500 Mating cycle	· Alloy 0.8μm minimu s	m	R S	Nominal         34.9±0.3         0.07+0.1/-0.15         32.5Max         31.8±0.4         2.2+0.9/-0.1         M15x1-6g		SOURIAU shall due to a use the Specification (profess	
		-65°C to +200°C 500 hours					A 30-09-20 ISS DATE Designed By:	16 First Release Latest modificat	
_	BASIC SERIES: SHELL TYPE :Jam nut Re	8D eceptacle	7 - 11	S 02 B A			TITLE SCALE NA		
	CONTACT TYPE : Standa					ORIENTATION	- SUURIA	SOURIAU WWW	
	SHELL SIZE : 11 PLATING : S = Nic								
				I			A3		
l	Н		G	F	E		D	С	

	4
LAYOUT SHOWN AS EXAMPLE	3
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D711S02BA	2
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series	
General linear Tolerances: ±       NPRDS / PROJECT         859       859         W.SOURIAU.COM       This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
SOURIAU DRG N°SHEET8D711S02BA-C1/2BA	

Centerior     Set tanta       Image: Set tanta     Set tanta		0		m	ш	Q	т	F
Image: State Stat		JAM NUT RECEPTACLE (TYPE 7)					-X (2	4
ØC       20.96+0.25/-0         SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Partice or by a third party (professional recommendation, technical notice.)         Image: Source of the Partice						Contact location           X-axis         Y-axis           (mm)         (mm)           +.095 (2.41)         +.000 (.00)          095 (2.41)         +.000 (.00)	pos II Shell Arrangement	
N								ω
Not Listed         PN: 8D711S02BA         A       30-09-2016         First Release         ISS       DATE         Latest modification - by       MOD N°         Designed By:       Date:         CUSTOMER DRAWING         TITLE       Stainless Steel Receptacle 8D series         SCALE       General linear         NA       General linear         Tolerances:       859	ucts which does not comply with ither of the Parties or by a third party nendation, technical notice.)	due to a use of the Products which the Specifications issued by either of th (professional recommendation)					-	
ISS DATE Latest modification - by MOD N°   Designed By: Date: CUSTOMER DRAWING   TITLE Stainless Steel Receptacle 8D series   SCALE SCALE   NA 100 N°   Stainless NPRDS / PROJECT   Tolerances: 359	FR Not Listed	PN: 8D711S0	A 20.00.2016					N
NA Tolerances: <u>t</u> <b>859</b>	CUSTOMER DRAWING	E Latest modification - by Date:	ISS DATE Designed By:					_
SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or	Ces:     859       AU.COM     This document is the property of SOURIAU it must not be reproduced or	Tolerances:	NA					
FORMAT     SOURIAU DRG N°     SHEET       A3     8D711S02BA-C     2/2       H     G     F     E     D     C     B     A	IAU DRG N° SH 11S02BA-C 2	8D711S02	A3	E	F	G	H	