

CARMEN-S-C

~14° spot beam. Assembly with holder C compatible with LEDiL HEKLA.

SPECIFICATION:

Dimensions	Ø 69.5 mm
Height	41.5 mm
Fastening	socket
ROHS compliant	yes 🕕



MATERIALS:

Component	Type	Material	Colour	Finish
CARMEN-S	Single lens	PMMA	clear	
CARMEN-HLD-C	Holder	PC	black	


ORDERING INFORMATION:

» Box size: 476 x 273 x 292 mm

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP15774_CARMEN-S-C	Single lens	150	150	15	4.5




PRODUCT DATASHEET CP15774_CARMEN-S-C




See also our general installation guide: www.ledil.com/installation_guide












CITIZEN

CLU700/701/702/703

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 10.0° / 25.0° Efficiency 78 % Peak intensity 12.7 cd/lm LEDs/each optic Light colour White

F15255_HEKLA-SOCKET-C




CITIZEN

Required components:

LED CLU710/711 FWHM / FWTM 13.0° / 33.0° Efficiency 73 % Peak intensity 7.2 cd/lm LEDs/each optic 1

White Light colour Required components:

F15859_HEKLA-SOCKET-I




CITIZEN

CLU7A2/7A3 FWHM / FWTM 7.0° / 20.0° Efficiency 80 % Peak intensity 18.5 cd/lm

LEDs/each optic Light colour White Required components:

F15255_HEKLA-SOCKET-C




CITIZEN


CLU7B2 FWHM / FWTM 6.0° / 19.0° Efficiency 80 % Peak intensity 21.7 cd/lm

LEDs/each optic White Light colour Required components:


F15255_HEKLA-SOCKET-C





























SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM 15.0° / 36.0°
Efficiency 74 %
Peak intensity 6 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C



SAMSUNG

 LED
 LC010C G2

 FWHM / FWTM
 9.0° / 24.0°


 Efficiency
 77 %

 Peak intensity
 13.1 cd/lm

LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C





SAMSUNG


LED LC010T (Tunable White)

FWHM / FWTM 15.0° / 35.0° Efficiency 71 % Peak intensity 5.8 cd/lm LEDs/each optic 1

Light colour Tunable White

Required components: C16142_HEKLA-SOCKET-K

Bender Wirth: 501 Typ L8




SAMSUNG


LED LC020C
FWHM / FWTM 12.0° / 31.0°
Efficiency 76 %
Peak intensity 8.2 cd/lm
LEDs/each optic 1
Light colour White

Required components: F15848_HEKLA-SOCKET-G












TRIDONIC

LED SLE G7 LES13
FWHM / FWTM 20.0° / 45.0°
Efficiency 69 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour White

Required components: F15859_HEKLA-SOCKET-I




XICATO

LED XOB 6 mm
FWHM / FWTM 10.0° / 26.0°
Efficiency 76 %
Peak intensity 11.4 cd/lm

LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C





XICATO

LED XOB 9.8 mm FWHM / FWTM 14.0° / 34.5 + 34.0°

Efficiency 74 %
Peak intensity 6.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C






XICATO

LED XTM - 19mm LES FWHM / FWTM 23.0° / 60.0° Efficiency 66 %

Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C16058_XTM-ADAPTER-50-C





bridgelux

 LED
 VERO13

 FWHM / FWTM
 16.0° / 42.0°


 Efficiency
 70 %

Peak intensity 4 cd/lm LEDs/each optic 1

Light colour White

Required components:

C16142_HEKLA-SOCKET-K



CITIZEN


LED CLL02x/CLU02x (LES10)

FWHM / FWTM 14.0° / 26.0° Efficiency 50 % Peak intensity 6.4 cd/lm LEDs/each optic 1

LEDs/each optic 1
Light colour White

Required components:

F15859_HEKLA-SOCKET-I C16752_CARMEN-70-SHD



CITIZEN

LED CLU700/701/702/703


 FWHM / FWTM
 10.0° / 19.0°

 Efficiency
 54 %

 Peak intensity
 13.8 cd/lm

LEDs/each optic 1
Light colour White

Required components: F15255_HEKLA-SOCKET-C C16752_CARMEN-70-SHD



CITIZEN

LED CLU712/713 FWHM / FWTM 14.0° / 30.0°

Efficiency 75 %


Peak intensity 8.1 cd/lm

LEDs/each optic 1

Light colour White

Required components:

F15859_HEKLA-SOCKET-I





White


CITIZEN

LED CLU712/713
FWHM / FWTM 12.0° / 24.0°
Efficiency 51 %

Peak intensity 7.6 cd/lm LEDs/each optic 1

Light colour
Required components:

F15859_HEKLA-SOCKET-I C16752_CARMEN-70-SHD



CITIZEN


LED CLU7A2/7A3

 $\begin{array}{lll} \text{FWHM} \ / \ \text{FWTM} & 8.0^{\circ} \ / \ 16.0^{\circ} \\ \text{Efficiency} & 55 \ \% \\ \text{Peak intensity} & 18.2 \ \text{cd/lm} \end{array}$

LEDs/each optic 1
Light colour White

Required components:

F15255_HEKLA-SOCKET-C C16752_CARMEN-70-SHD




CREE - LED

LED CMA1840 FWHM / FWTM 22.0° / 47.0°

Efficiency 66 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White

Required components: Bender Wirth: 637a Hekla




CREE & LED

LED CMU15xx FWHM / FWTM 21.0° / 46.0°

Efficiency 65 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438_HEKLA-G2-I






CREE \$\text{LED}

LED CXA/B 15xx
FWHM / FWTM 12.9° / 28.4°
Efficiency 0 %
Peak intensity 9.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:


F15256_HEKLA-SOCKET-D



WNICHIA

LED COB T-Type
FWHM / FWTM 11.0° / 24.0°
Efficiency 78 %
Peak intensity 12.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15848_HEKLA-SOCKET-G




SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM 16.0° / 34.0°
Efficiency 73 %
Peak intensity 6.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17435_HEKLA-G2-C







SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

FWHM / FWTM 16.0° / 34.0°
Efficiency 73 %
Peak intensity 6.3 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17435_HEKLA-G2-C








SAMSUNG

LED LC010C
FWHM / FWTM 11.0° / 24.0°
Efficiency 78 %
Peak intensity 13 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17435_HEKLA-G2-C





PRODUCT DATASHEET CP15774_CARMEN-S-C

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405, Block B **Casic Motor Building** Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where to buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy