



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| D  | 6mm              |
| H  | 9.9mm            |
| S  | 2.54mm +/-0.38mm |
| LL | 12.7mm +/-1.26mm |
| H0 | 18mm MIN         |
| F  | 0.5mm +/-0.05mm  |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 305mm |
| Packaging Quantity | 1000       |

### General Information

|             |   |
|-------------|---|
| Series      | T350                                      |
| Dielectric  | MnO2 Tantalum                             |
| Style       | Radial                                    |
| Description | Radial, Solid Tantalum, Conformal, Dipped |
| Features    | Low Leakage                               |
| RoHS        | Yes                                       |
| Termination | Tin                                       |
| AEC-Q200    | No  |
| Notes       | Longest Lead Is Positive.                 |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 22 uF  |
| Capacitance Tolerance | 20%  |
| Voltage DC            | 16 VDC (85C), 10 VDC (125C), 0.16 VDC (125C Reverse) |
| Temperature Range     | -55/+125°C   |
| Dissipation Factor    | 6%   |
| Leakage Current       | 2.6 uA   |