




.XXX ±0.05

\ _	
4   [7 [	OR
$\mathbb{N}$	








NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


DIELECTRIC

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED




OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	ĺ
INSULATOR RESISTANCE:	5000MΩ min.	



					SW REFERENCE NO.: 629 COMBO ASSEMBLY					
	COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		19			
			CHECKED:		DATE:					
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE: (IN C.A.D. 1:	1)	SHEET 1	OF	2			
	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 629-17W22		.240-5TD		ISSUE			
YOUR CONNECTION TO	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER:	629-17W2	2240-5TD		1			

1000V AC rms





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

