

## DAISY-28X1-W2-B

~50° wide beam with tighter cutoff. Variant with 7X1 lenses.

### SPECIFICATION:

Dimensions	1140.0 x 40.0 mm
Height	20.2 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ

### MATERIALS:

Component	Type	Material	Colour	Finish
C16989_DAISY-7X1-W2	Linear lens	PMMA	clear	
C17482_DAISY-28X1-SHD-WHT-MATT	Shade	PC	white	matt
C17481_DAISY-28X1-SHD-MATT	Shade	PC	black	matt
C16783_DAISY-28X1-SHD-WHT	Shade	PC	white	gloss
C16585_DAISY-28X1-SHD	Shade	PC-ABS	black	gloss


### ORDERING INFORMATION:

#### Quantities for one set:

Linear lens	4
Shade	1



Component		Qty in box	MOQ	MPQ	Box weight (kg)
C16989_DAISY-7X1-W2 » Box size: 400 x 300 x 300 mm	Linear lens	312	192	24	7.0
C17481_DAISY-28X1-SHD-MATT » Box size: 1185 x 385 x 125 mm	Shade	48	48	48	8.6
C16585_DAISY-28X1-SHD » Box size: 1185 x 385 x 125 mm	Shade	48	48	48	8.4
C17482_DAISY-28X1-SHD-WHT-MATT » Box size: 1185 x 385 x 125 mm	Shade	48	48	48	8.7
C16783_DAISY-28X1-SHD-WHT » Box size: 1185 x 385 x 125 mm	Shade	48	48	48	8.8




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)


### OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 58.0° / 69.0°  
 Efficiency 92 %  
 Peak intensity 1.2 cd/m  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16783\_DAISSY-28X1-SHD-WHT





LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 57.5° / 68.5°  
 Efficiency 91 %  
 Peak intensity 1.2 cd/m  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17537\_DAISSY-28X1-SHD-MET-MATT



LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 57.5° / 68.0°  
 Efficiency 85 %  
 Peak intensity 1.2 cd/m  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17481\_DAISSY-28X1-SHD-MATT




LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 57.5° / 68.5°  
 Efficiency 92 %  
 Peak intensity 1.2 cd/m  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17482\_DAISSY-28X1-SHD-WHT-MATT





### OPTICAL RESULTS (MEASURED):




LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 58.0° / 68.0°  
 Efficiency 85 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16585\_DAISY-28X1-SHD





LED LIGHT ENGINE DAISY 112 LEDs 1,140mm x 20mm  
 FWHM / FWTM 57.5° / 69.0°  
 Efficiency 92 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17527\_DAISY-28X1-SHD-MET



LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 69.0 + 68.0°  
 Efficiency 84 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17481\_DAISY-28X1-SHD-MATT




LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 70.0 + 68.5°  
 Efficiency 91 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17482\_DAISY-28X1-SHD-WHT-MATT



### OPTICAL RESULTS (MEASURED):



#### MST *Your solutions*

LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 69.0 + 68.0°  
 Efficiency 84 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16585\_DAISSY-28X1-SHD




#### MST *Your solutions*

LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 70.0 + 68.5°  
 Efficiency 90 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17527\_DAISSY-28X1-SHD-MET




#### MST *Your solutions*

LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 70.0 + 68.5°  
 Efficiency 91 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16783\_DAISSY-28X1-SHD-WHT



#### MST *Your solutions*


LED LinLED 1120x28mm 4400lm 8x0 4C Opt G1  
 FWHM / FWTM 59.5 + 58.0° / 70.0 + 68.5°  
 Efficiency 90 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C17537\_DAISSY-28X1-SHD-MET-MATT



### OPTICAL RESULTS (MEASURED):



#### SAMSUNG

LED LM28xB Series  
 FWHM / FWTM 50.0° / 65.0°  
 Efficiency 92 %  
 Peak intensity 1.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C16783\_DAISSY-28X1-SHD-WHT





#### SAMSUNG



LED LM28xB Series  
 FWHM / FWTM 50.0° / 65.0°  
 Efficiency 89 %  
 Peak intensity 1.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C16585\_DAISSY-28X1-SHD



LED PassivePAQ-L-2F35-SSA3-5.4K-840-3-DC  
 FWHM / FWTM 65.0° / 75.0°  
 Efficiency 87 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16783\_DAISSY-28X1-SHD-WHT




LED PassivePAQ-L-2F35-SSA3-5.4K-840-3-DC  
 FWHM / FWTM 65.0° / 73.0°  
 Efficiency 76 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:  
 C16585\_DAISSY-28X1-SHD



### OPTICAL RESULTS (SIMULATED):

#### SAMSUNG

LED	LM28xB Series
FWHM / FWTM	54.0 + 58.0° / 68.0 + 72.0°
Efficiency	90 %
Peak intensity	1.2 cd/lm
LEDs/each optic	4
Light colour	White
Required components:	
	C16783_DAISY-28X1-SHD-WHT





### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)