т (<u></u>	m D	0			
			SHOWN AS EXAMPLE		
		LATOUT			
Keying Shown as example					
CHARACTERISTICS Connector -Standard : Based on MIL-DTL-38999 Series III Dim	r dimension Nominal				
-Shell Material : Aluminium	25 Max		liable for any non-conformity of	vr damaga	-
-Shell Plating : Nickel Z VV THREAD	31 Max M15x1-6g		 liable for any non-conformity c Products which does not comp 		
-Insulator : Thermoplastic	<u> </u>		d by either of the Parties or by a		
-Contacts : Copper Alloy		(professional r	ecommendation, technical notion	ce.)	
-Seals & Grommet : Silicon Elastomer				ion & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed	:
-Durability : 500 Mating cycles		DNI	8D511F02SDL		
-Delivered without Souriau contacts					
-Temperature Range -65°C to +200°C	Α	15-10-2016 First Release			
-Salt Spray : 48 hours	ISS	DATE Latest modification - by	,	MOI	D N°
	Designed				
	г	TITLE Aluminium Plug 8D series			
	SCAL	E c c	eneral linear	NPRDS / PROJECT	
BASIC SERIES: 8D 5 - 11 F 02 S D L			olerances:	859	
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Contacts NA		±	This document is the property of	
CONTACT TYPE : Standard Crimp Contact		URIAU WWW.SO	URIAU.COM	SOURIAU it must not be reproduced or	
SHELL SIZE : 11 CONTAC	CT TYPE : SOCKET(500 Matings)			communicated without permission	
PLATING : F = Nickel	CONTACT LAYOUT : 11-02		DURIAU DRG N°		EET
	A3	8	D511F02SDL-C	1/	/2
H G F	E D	С	В	A	

r	Ŧ	۵	н т	m	D	0	
		Contact Layout					
4	. X. .0. (2.	+Y IB IA +Y +X 95 -Y .095 (2.41mm)					
	Cont posit ID A B Shell Arrangement no. 11 -2	X-axis Y-axis (mm) (mm) +.095 (2.41) +.000 (.00) 095 (2.41) +.000 (.00)					
ω							
	+					SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts w by either o
N						PN: 8[Count FR D511
					A 15-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
					SCALE	Gene	Alumin eral linear erances:
→					SOURIA		±
				,	FORMAT A3	SOL 8D	JRIAL 511F
	Н	G	F	E	D	C	

