




LVO-MCL-23-A

Ruland LVO-MCL-23-A, 23mm One-Piece Shaft Collar with Clamping Lever, Aluminum Collar with Zinc Plated Lever, 45mm OD, 15mm Width





Description

Ruland LVO-MCL-23-A is a one-piece quick clamping shaft collar with clamping lever with a 23mm bore, 45mm OD, and 15mm width. It is made from MCL-23-A and LF45-CL-M6:18-ZS. The clamp style design does not mar the shaft, is easy to remove, and is indefinitely adjustable. The threaded stud on the lever is used in place of standard collar hardware. When combined, the two parts create a shaft collar that requires no tools to install, remove, or reposition and is ideally suited for packaging, printing, and other applications where frequent setup changes and adjustments are needed. Once the lever is installed in the shaft collar, users simply turn the lever until they meet their desired torque. The adjustable lever can be reposition by the user without the loss of holding power by lifting the handle and twisting it 40° to lock it in a new position. This allows for use in space constrained environments where 360° rotation is not possible to fully seat the lever. MCL-23-A is made from high-strenth 2024 aluminum. LF45-CL-M6:18-ZS has a zinc plated steel handle and stainless steel threaded stud. This material combination allows for a lightweight durable quick clamping and release component that is suitable for most industrial applications. The lever is orange for safety and ease of identification. MCL-23-A is manufactured by Ruland and LF45-CL-M6:18-ZS is manufactured by Otto Ganter. LVO-MCL-23-A is RoHS3 and REACH compliant.

Product Specifications

Width (W)15 mmWidth Tolerance+0.076 mm / -0.254 mmLever Length L145 mmLever Height H238.5 mmHub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque16 NmScrew Location (R)17.50 mmNumber of Screws1 eaCollar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.197300UPC634529293744Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Bore (B)	23 mm	Bore Tolerance	+0.050 mm / +0.012 mm
Lever Length L145 mmLever Height H238.5 mmHub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque16 NmScrew Location (R)17.50 mmNumber of Screws1 eaCollar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.197300UPC634529293744Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Outer Diameter (OD)	45 mm	Center to Lever Top H1	38.8 mm
Hub Diameter DH13 mmSleeve Length L218 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM6Hex Wrench Size5.0 mmSeating Torque16 NmScrew Location (R)17.50 mmNumber of Screws1 eaCollar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.197300UPC634529293744Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65WARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Width (W)	15 mm	Width Tolerance	+0.076 mm / -0.254 mm
Recommended Shaft Tolerance +0.000 mm / -0.013 mm Thread TH M6 Hex Wrench Size 5.0 mm Seating Torque 16 Nm Screw Location (R) 17.50 mm Number of Screws 1 ea Collar Part Number MCL-23-A Lever Part Number LF45-CL-M6:18-ZS-Q Collar Material Aluminum Collar Finish Bright Handle Color Orange Handle Material Zinc Handle Finish Powder Coated Insert and Screw Material 303 Stainless Steel Manufacturer Ruland Manufacturing Country of Origin Shaft Collar - USA Lever - Germany Weight (lbs) 0.197300 UPC 634529293744 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Lever Length L1	45 mm	Lever Height H2	38.5 mm
Hex Wrench Size5.0 mmSeating Torque16 NmScrew Location (R)17.50 mmNumber of Screws1 eaCollar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.197300UPC634529293744Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Hub Diameter DH	13 mm	Sleeve Length L2	18 mm
Screw Location (R)17.50 mmNumber of Screws1 eaCollar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.197300UPC634529293744Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Recommended Shaft Tolerance	+0.000 mm / -0.013 mm	Thread TH	M6
Collar Part NumberMCL-23-ALever Part NumberLF45-CL-M6:18-ZS-OCollar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.197300UPC634529293744Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Hex Wrench Size	5.0 mm	Seating Torque	16 Nm
Collar MaterialAluminumCollar FinishBrightHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.197300UPC634529293744Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Screw Location (R)	17.50 mm	Number of Screws	1 ea
Handle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.197300UPC634529293744Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Collar Part Number	MCL-23-A	Lever Part Number	LF45-CL-M6:18-ZS-O
Handle Finish Powder Coated Insert and Screw Material 303 Stainless Steel Manufacturer Ruland Manufacturing Country of Origin Shaft Collar - USA Lever - Germany Weight (Ibs) 0.197300 UPC 634529293744 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Collar Material	Aluminum	Collar Finish	Bright
Manufacturer Ruland Manufacturing Country of Origin Shaft Collar - USA Lever - Germany Weight (Ibs) 0.197300 UPC 634529293744 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Handle Color	Orange	Handle Material	Zinc
Lever - Germany Weight (lbs) 0.197300 UPC 634529293744 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 WARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Handle Finish	Powder Coated	Insert and Screw Material	303 Stainless Steel
Weight (lbs) 0.197300 UPC 634529293744 Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Manufacturer	Ruland Manufacturing	Country of Origin	Shaft Collar - USA
Tariff Code 8483.60.8000 UNSPC 31162811 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicatio Prop 65 AWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and				Lever - Germany
Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicatioProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and	Weight (Ibs)	0.197300	UPC	634529293744
Prop 65	Tariff Code	8483.60.8000	UNSPC	31162811
· · · · · · · · · · · · · · · · · · ·	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65		pose you to the chemical Soots, Ben	zene, Lead, Nickel (metallic), and