



[www.aopled.com](http://www.aopled.com)

**American Opto Plus LED Corp.**  
**0.56" SMD Type LED Display**  
**SMA561LY-ST-1.5 G/W**  
**SMC561LY-ST-1.5 G/W**

● **EDIT HISTORY**

Version A: Jul. 15, 2015

Preliminary spec.

Version B: Jul. 22, 2015

1. Modify mechanical dimensions.
2. Modify typical internal equivalent circuit.

Version C: Apr. 25, 2019

1. Modify absolute maximum rating.
2. Modify forward voltage max data, from 2.6V to 2.4V.
3. Modify mechanical dimensions.
4. Modify curve graph.
5. Add packing spec.



[www.aopled.com](http://www.aopled.com)

# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display

### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

#### ● FEATURES

- 0.56 inch (14.22 mm) Digit Height.
- Low current operation.
- Super thin SMD type.
- Gray face, White segment.
- RoHS compliant, Pb Free.

#### ● DESCRIPTION

The SMA561LY-ST-1.5 G/W & SMC561LY-ST-1.5 G/W

Are 0.56 inch (14.22mm) height single digit 7-segment display.

This device utilizes Super Bright Yellow LED chip which are made from AlGaInP on a transparent GaAs substrate.

The display has Gray face, White segment.

#### ● DEVICE

PART NO	DESCRIPTION
SMA561LY-ST-1.5 G/W	Common Anode
SMC561LY-ST-1.5 G/W	Common Cathode

**RoHS Compliance**



**Pb free.**





[www.aopled.com](http://www.aopled.com)


# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display

### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

## MECHANICAL DIMENSIONS



### NOTE:

Dimension in millimeters (inches),

And tolerances are  $\pm 0.25\text{mm}$  (.01") specified.



[www.aopled.com](http://www.aopled.com)



# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display


### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

#### ● TYPICAL INTERNAL EQUIVALENT CIRCUIT



SMA561LY-ST-1.5 G/W



SMC561LY-ST-1.5 G/W



[www.aopled.com](http://www.aopled.com)

**American Opto Plus LED Corp.**  
**0.56" SMD Type LED Display**  
**SMA561LY-ST-1.5 G/W**  
**SMC561LY-ST-1.5 G/W**

● **LY: SUPER BRIGHT YELLOW (AlGaInP/GaAs)**

ABSOLUTE MAXIMUM RATING AT  $T_a=25^{\circ}\text{C}$

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	$P_{AD}$	48	mW
Continuous forward current	$I_{AF}$	20	mA
Peak current (duty cycle 1/10, 1kHz)	$I_{PF}$	40	mA
Reverse voltage	$V_R$	5	V
Operating temperature	$T_{OPR}$	-40 to +85	$^{\circ}\text{C}$
Storage temperature	$T_{STG}$	-40 to +85	$^{\circ}\text{C}$

ELECTRICAL - OPTICAL CHARACTERISTICS AT  $T_a=25^{\circ}\text{C}$

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	$V_F$	$I_F=20\text{mA}$	-	2.1	2.4	V
Reverse Current, (Per Dice)	$I_R$	$V_R=5\text{V}$	-	-	10	$\mu\text{A}$
Peak Wavelength	$\lambda_P$	$I_F=20\text{mA}$	-	593	-	nm
Dominant Wavelength	$\lambda_D$	$I_F=20\text{mA}$	585	-	595	nm
Luminous Intensity	$I_V$	$I_F=10\text{mA}$	10	-	40	mcd
Spectral Line Half-Bandwidth	$\Delta\lambda$	$I_F=20\text{mA}$	-	20	-	nm



[www.aopled.com](http://www.aopled.com)

**American Opto Plus LED Corp.**  
**0.56" SMD Type LED Display**  
**SMA561LY-ST-1.5 G/W**  
**SMC561LY-ST-1.5 G/W**

● **LY: BIN GRADE (Unit : mcd) 10mA**

Super Bright Yellow	G	H	I
	10.0 – 20.0	20.1 – 30.0	30.1 – 40.0

● **LY: HUE GRADE ( $\lambda_D$  : nm)**

1	2	3
585.0 – 588.0	588.1 – 592.0	592.1 – 595.0

● **AVAILABLE BIN / HUE TABLE**

G1	H1	I1
G2	H2	I2
G3	H3	I3



[www.aopled.com](http://www.aopled.com)

# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display

### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

## ● LY: SUPER BRIGHT YELLOW (AlGaInP/GaAs) CURVE

Typical Electro-optical Characteristic Curves  
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1-Relative Intensity VS. Wavelength




Fig.2-Relative Luminous Intensity vs. Forward Current




Fig.3-Forward Current vs. Forward Voltage




Fig.4-Relative Intensity(@20mA) vs. Ambient Temperature




Fig.5-Forward Voltage(@20mA) vs. Ambient Temperature




Fig.6-Dominant Wavelength(@20mA)  
VS. Ambient Temperature




Fig.7-Max. Allowable DC Current  
VS. Ambient Temperature



[www.aopled.com](http://www.aopled.com)

# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display


### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

## ● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).  
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

## ● SOLDERING IRON

Basic spec is  $\leq 4$  sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller Than 15W, and temperature should be controllable. Surface temperature Of the device should be under 230°C.

## ● REWORK

- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.





[www.aopled.com](http://www.aopled.com)


# American Opto Plus LED Corp.

## 0.56" SMD Type LED Display


### SMA561LY-ST-1.5 G/W

### SMC561LY-ST-1.5 G/W

#### ● REEL DIMENSIONS



#### ● PACKING & LABEL SPECIFICATIONS



The leader and trailer length of actual tape with no component in it are 400 mm each.

#### ● STORAGED CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)