




T556B107K060AT

T556, Tantalum, Polymer Tantalum, HRA, 100 uF, 10%, 60 VDC, N/A, 100 mOhms, Height Max = 9.6mm

BOTTOM VIEW



CATHODE (-) END VIEW



SIDE VIEW

Click [here](#) for the 3D model.

Dimensions

| | |
|---|-----------------|
| L | 24.5mm +/-0.5mm |
| W | 8.5mm +/-0.5mm |
| H | 9.1mm +/-0.5mm |
| S | 3mm +/-0.3mm |
| F | 4.2mm +/-0.5mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Box |
| Packaging Quantity | 100 |

General Information

| | |
|------------------|--------------------------------------|
| Series | T556 |
| Dielectric | Polymer Tantalum |
| Style | SMD Chip |
| RoHS | No |
| SCIP Number | 43449f08-bd3e-4b72-a04c-6ca7dd4144ff |
| Termination | Tin |
| AEC-Q200 | No |
| Component Weight | 5.54 g |
| Shelf Life | 156 Weeks |

Specifications

| | |
|-----------------------|-----------------------------------------|
| Capacitance | 100 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 60 VDC, 39.6 VDC (125°C), 69 VDC (85°C) |
| Temperature Range | -55/+125°C |
| Life | 2000 Hrs |
| Dissipation Factor | 5% (120Hz 25C) |
| Failure Rate | N/A |
| Resistance | 100 mOhm (100kHz 25C) |
| Ripple Current | 1660 mAmps (40kHz 85C) |
| Leakage Current | 45 uA (5min 25°C) |