



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 18mm +0.3/-0.5mm |
| H  | 11mm +0.1/-0.5mm |
| T  | 5mm +0.2/-0.5mm  |
| S  | 15mm +/-0.4mm    |
| LL | 4mm +2mm         |
| F  | 0.6mm +/-0.05mm  |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 2000      |

### General Information

|                  |                              |
|------------------|------------------------------|
| Series           | R41B                         |
| Dielectric       | Metallized Polypropylene     |
| Style            | Radial                       |
| Features         | Automotive Grade, EMI Safety |
| RoHS             | Yes                          |
| Lead             | Cut                          |
| Safety Class     | Y2                           |
| Qualifications   | AEC-Q200, ENEC, UL, cUL, CQC |
| AEC-Q200         | Yes                          |
| THB Performance  | Yes                          |
| Component Weight | 1.2 g                        |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 0.01 uF      |
| Capacitance Tolerance | 10%          |
| Voltage AC            | 350 VAC (Y2) |
| Temperature Range     | -40/+125°C   |
| Rated Temperature     | 125°C        |
| Dissipation Factor    | 0.3% 1KHz    |
| Insulation Resistance | 100 GOhmS    |
| Max dV/dt             | 600 V/us     |