



注記 NOTES

- 材質 MATERIAL
 端子：無酸素銅、錫めっき
 TERMINAL: OXYGEN-FREE COPPER, TIN PLATING
 ろう付け部：りん銅ろう
 PART OF BRAZING : COPPER PHOSPHORUS BRAZING FILLER METALS
- 適用電線 APPLICABLE WIRE RANGE

単線 SOLID WIRE	撚線 STRANDED WIRE
1.14 ~ 1.82 mm	1.04 ~ 2.63 mm ²

⚠ JIS認定品にのみ刻印。
 DIE STAMPED MARK IS ALLOWED ONLY
 FOR JIS FILED PRODUCTS.

JIS	0.8	6.4 ^{+0.4}	22	7	4.1	2.3	4.2	15	2	6	50225-7412
JIS		5.3 ^{+0.2}	17.5	7				9.5		5	50225-7312
JIS		4.3 ^{+0.2}	17	6				8.5		4	50225-7212
JIS		3.7 ^{+0.2}		4				6.6		3.5	50225-7112
⚠	t	ϕd_2	L	F	E	ϕd_1	ϕD	B	ϕ	呼 NOMINAL SIZE	ENG. NO.

RELEASED EC NO: J2007-0312 DRW: H.YAJIMA 2007/05/17 CHK: K.KASAHARA 2007/05/18 APPR: NUKITA 2007/05/18	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	10 UNDER	± 0.2	DRAWN BY H. YAJIMA	DATE 2006/10/25	TITLE RING TERMINAL			
	10 OVER 30 UNDER	± 0.25	CHECKED BY K. KASAHARA	DATE 2006/10/25	MATERIAL NO. SEE CHART			
	30 OVER	± 0.3	APPROVED BY N. UKITA	DATE 2006/10/25	DOCUMENT NO. SD-50225-001			
	ANGULAR	± 3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		SHEET NO. 1 OF 1	