


Coaxial PCB Connector 85_MCX-50-0-16/111_N

Description

Right angle PCB jack

Interface Standards

IEC 60169-36_CECC 22220



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 6 GHz |

Mechanical Data

| | |
|---------------------|---------------|
| Board mounting type | through holes |
| Weight | 0.0017 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPRO Plating |
| Body | Brass | SUCOPRO Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00012853 |
| Catalogue drawing | DCA-00012855 |

Ordering Information

| | |
|-----------------------|-----------------------|
| Tape and Reel package | 85_MCX-50-0-16/111_NM |
| Bulk 100 pcs package | 85_MCX-50-0-16/111_NH |
| Single package | 85_MCX-50-0-16/111_NE |

Remarks

PCB connector with stand-offs