



Screw Terminal Blocks

2000/ 2

terminal block, 2 pole, insulating material: PA, cross-section rating: 16.0 mm², pin spacing: 14.50 mm, mounting hole diameter: 4.3 mm, fixing: screw, voltage rating: 500 V, current rating: 76 A



Order Info

reference number (ref.no.)	128202
PU	120
EAN	4028012106479

Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	16.0 mm ²
connection type	screw

Technical Data

voltage rating	500 V
current rating	76 A
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	16.0 mm ²
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0-10.5 mm
assembly contact screw	1,0x5,5 / ⤵ 2,0 Nm
mounting hole diameter	4.3 mm
pin spacing	14.50 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

2000 BZ/ 2	191802
ZEL 110	196420