


NOTES:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED -55°C ~ 125°C 30A (CURRENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT $10m\Omega$ MAX. 5000MΩ min. DIELECTRIC

1000V AC rms

SW REFERENCE NO .: 630 COMBO ASSEMBLY COMBINATION D-SUB DRAWN: C.B DATE: JAN. 01/2019 CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS OF 2 SCALE: (IN C.A.D. 1:1) SHEET 1 EDAC INC ARE THE PROPERTY OF EDAC INC., AND TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 630-3WK3650-3T5 ISSUE DRAWING NUMBER: OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS 1 YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 630-3WK3650-3T5 WITHOUT WRITTEN PERMISSION.






20.33 10.67

> THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

		\sim	5	
				D
Ý			5	
	Ľ			



.XX

WITHSTANDING VOLTAGE:

±0.13

.XXX ±0.05

