






THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.









NOTES:

MATERIAL: HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 **BLACK IN COLOUR** STEEL, NICKEL PLATED SHELL: CONTACT: COPPER ALLOY, 15µ GOLD PLATING

OPERATING TEMPERATURE: -55°C ~ 85°C

3A PER CONTACT CURRENT RATING: CONTACT RESISTANCE: $25m\Omega$ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

		SW REFERENCE NO.: 661 ASSEMBLY						
	661 SERIES D-SUB (DRAWN: C.B		DATE: /	AUG. 01/2	2018		
			CHECKED:		DATE:			
TO VES ICY.	EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1		SHEET	1 OF	1	
			DRAWING NUMBER:	R: 661-009-364-050			ISSUE	
			PART NUMBER:	661-009-3	364-050		1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVE 2011/65/EU FOR RoHS COMPLIANC