ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב	т п		0	₿ >		
5			LAYOUT SHOWN AS EXAMP	LE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max					
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles			FR Not Listed			
-Delivered with Souriau contacts and Accessories			PN: 8D511W01SA			
-Temperature Range : -65°C to +175°C						
-Salt Spray : 500 hours		A 17-10-2016	First Release			
Mass : 17.92 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING) N°	
		TITLE	TITLE Aluminium Plug 8D series			
		SCALE	General linear	NPRDS / PROJECT		
BASIC SERIES: 8D 5 - 11 W 01 SHELL TYPE : Plug with RFI Shielding	1 S A	NA	Tolerances:	859		
				This document is the property of		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : A SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM it must not be reproduce communicated without per			
PLATING : W = Olive drab Cadmium		YOUT : 11-01		communicated without permission		
PLATING . W = Onve drab Caumium	CONTACT LA	A3	SOURIAU DE			
		. A.5	8D511W01	SA-C 1/2	12	

F	Ŧ	G	ات	m	D	0
		Contact Layout				
4	/	01				
	(1#12				
	Ctc A	11-01 X Y 0 0				
ω						
	_					SOURIAU shall not be liable for an
						due to a use of the Products whether of the Specifications issued by either of (professional recommendat
CJ						PN: 8D511V
					A 17-10-2 ISS DATE	016 First Release
					Designed By:	Date:
-					SCALE NA	General linear Tolerances: ±
					FORMAT	
					A3	SOURIAU 8D511W
	Н	G	F	E	D	C

