Cartridge Fuses





MCASE+™ Cartridge Fuses

MCASE+[™] Cartridge Fuses Rated 32V

The Unslotted MCASE+[™] Fuse is a cartridge style fuse up to 40A with female terminals for 2.8 mm male terminals. The Slotted MCASE+[™] Fuse is available in amperages up to 60A and can mate with larger male terminals (e.g., 6.3mm) or even mount directly to onto a busbar. It has a miniaturized footprint for optimal usage of space. It is a time delayed fuse and can handle inrush currents.

Specifications

Voltage Rating: Interrupting Ratings: Operating Temperature Range: Housing Material: Cover Material: Fuse Insertion Force: Extraction Force: Conforms to: 32 VDC 1000A @ 32 VDC -40°C to +125°C PPA-GF33 PA66 50N (11.2lbf) Typical 4N Min. (0.9 lb). I 24.5N Max. (5.5 lb) SAE 2741 and ISO 8820-4 in reference to electrical, mechanical and environmental performance requirements

600

Time-Current Characteristics

0.04s / 1s


Ordering Information

Part Number	Package Size	% of Rating	Opening Time Min / Max
0695xxx.PXPS Slotted	2000	110	100hrs /
		135	60s / 1800s
0695xxx.PXP Unslotted	2000	200	2s / 60s
		350	0.2s / 7s


Ratings

Part Number	Туре	Current Rating* (A)	Housing Material Color	Max. Voltage Drop (mV)	Cold Resistance $(\mathbf{m}\Omega)$	l²t (A²s)	
0695015.PXP	Unslotted	15		125	5.1	310	
0695020.PXP	Unslotted	20		125	3.4	750	
0695025.PXP	Unslotted	25		125	2.5	1300	
0695030.PXP	Unslotted	30		120	1.8	970	
0695040.PXP	Unslotted	40		120	1	1550	
0695015.PXPS	Slotted	15		125	5.1	310	
0695020.PXPS	Slotted	20		125	3.4	750	
0695025.PXPS	Slotted	25		125	2.5	1300	
0695030.PXPS	Slotted	30		120	1.8	970	
0695040.PXPS	Slotted	40		120	1.1	1550	
0695050.PXPS	Slotted	50		120	0.8	4000	
0695060.PXPS	Slotted	60		115	0.6	8500	
* The performance of the male terminal is critical to ensuring the fuse will function as							

The performance of the male terminal is critical to ensuring the fuse will function as designed. The current-carrying capability of the mating terminal must be verified to ensure proper system operation.



Temperature Rerating Curve



Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages otherwise agreed by Littelfuse in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.

Time-Current Characteristic Curves