

Specification Sheet

Part Number: 151-01122



Separates bundles to help prevent chafing and wear.

Single bundles can be mounted on top of the mount, or two bundles can be separated using the two side saddles; giving the mount versatility.

Low profile design allows mount to be placed in areas where space is limited.

Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA66HIRHSUV, Black, 500/pkg

Article Number 151-01122

Type LPM25

Color Black (BK)

Quantity Per bag

Product Description Low Profile Mounts secure bundles close to mounting surfaces, making

them ideal for applications where bundle mounting space is limited. These are secured with a .25" mechanical fastener, and have a counter bore for easy access with a socket which can be torqued up to 100

in/lbs. The mount accommodates cable ties up to .5" in width.

Short Description Low Profile Screw Mount, 1.8" x 0.98", 0.25" Hole, PA66HIRHSUV,

Black, 500/pkg

Global Part Name LPM25-PA66HIRHSUV-BK

Length L (Imperial)	1.8
Length L (Metric)	45.1
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.98
Width W (Metric)	24.9
Cable Ties	T50 - T250
Height H (Imperial)	0.66
Height H (Metric)	16.7
Cable Tie Width Max (Imperial)	0.53
Cable Tie Width Max (Metric)	13.5
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.7 mm
Mounting Hole Diameter D Max (Metric)	6.7

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions