## ATGBICS HK-SFP-1.25G-20-1310 Hikvision Compatible Transceiver SFP 1000Base-BX-U (Tx1310nm/Rx1550nm, 20km, SMF, DOM)


**Brand :** ATGBICS **Product code:** HK-SFP-1.25G-20-1310-

**Product name:** HK-SFP-1.25G-20-1310 Hikvision Compatible Transceiver SFP 1000Base-BX-U (Tx1310nm/Rx1550nm, 20km, SMF, DOM)



HK-SFP-1.25G-20-1310 Hikvision Compatible Transceiver SFP 1000Base-BX-U (Tx1310nm/Rx1550nm, 20km, SMF, DOM)

ATGBICS HK-SFP-1.25G-20-1310 Hikvision Compatible Transceiver SFP 1000Base-BX-U (Tx1310nm/Rx1550nm, 20km, SMF, DOM):





| Performance   |  | Power   |  |
|---|--|---|--|
| SFP transceiver type * Fiber optic  Maximum data transfer rate * 1250 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Tx wavelength (max)  Rx wavelength (max)  Ethernet LAN  Ethernet interface type  Digital Diagnostics Monitoring  (CDM) | 1250 Mbit/s SFP  ✓  X LC BX-U 20000 m                              | Input voltage<br>Maximum voltage<br>Power consumption (typical)   | 3.3 V<br>3.5 V<br>1 W                        |
|   |  | Operational conditions  Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 70 °C<br>0 - 70 °C<br>-40 - 85 °C<br>0 - 95% |
|   | Storage relative humidity (H-H)  Weight & dimensions  Width  Depth | 0 - 95%<br>13.4 mm<br>56.5 mm   |  |
| (DDM) Features  |  | Height<br>Weight  | 8.5 mm<br>15 g                               |
| Product colour  Housing material  Plug and Play  Hot-swap  Easy to install  Country of origin  Brand compatibility  Certification  Silver  Metal  Metal  V  United Kingdom  Hikvision Digital Technology  CE, FCC, RoHS   | Packaging data  Number of products included  Package type          | 1 pc(s)<br>Box  |  |
|   | Hikvision Digital Technology                                       | Technical details  Sustainability compliance Sustainability certificates Doesn't contain  | ✓<br>RoHS<br>Lead                            |



5056468747112

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.