

## Socket terminal block - JBC 2,5/5 - 3240165

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



5-pos. socket terminal block with spring-cage connection, for toolless wiring with push-in connection method, for one and multi-strand conductors with a cross section of 0.5 to 2.5 mm<sup>2</sup>, insulation housing transparent.

### Your advantages

- ✓ Different cross sections can be wired together in a junction box connector
- ✓ Thanks to Push-in connection technology, the three junction box connector versions from Phoenix Contact enable tool-free wiring in a small amount of space
- ✓ Solid single-strand conductors with a cross section range of 0.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup> can be connected
- ✓ Solid multi-strand conductors (7 litz wires) with a cross section range of 1.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup> can be safely connected
- ✓ The transparent housing makes it easier to carry out a visual inspection of the terminal points, thereby increasing wiring safety
- ✓ Integrated test openings enable the use of test devices once wiring has been completed



### Key Commercial Data

Packing unit	100 pc
GTIN	
GTIN	4046356457958

### Technical data

#### General

Number of positions	5
Number of levels	1
Number of connections	5
Nominal cross section	2.5 mm <sup>2</sup>
Color	transparent
Insulating material	PC/PA
Flammability rating according to UL 94	V2
Maximum load current	24 A
Nominal current I <sub>N</sub>	24 A

# Socket terminal block - JBC 2,5/5 - 3240165

## Technical data

### General

Nominal voltage $U_N$	450 V
-----------------------	-------

### Dimensions

Width	26 mm
Length	15.6 mm
Height	8.9 mm
Depth	15.6 mm

### Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section solid min.	0.5 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section AWG min.	20
Conductor cross section AWG max.	14

### Standards and Regulations

Flammability rating according to UL 94	V2
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27141104
eCl@ss 11.0	27141104
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141104
eCl@ss 9.0	27141104

### ETIM

ETIM 3.0	EC001284
ETIM 4.0	EC001284
ETIM 6.0	EC000446
ETIM 7.0	EC000446

# Socket terminal block - JBC 2,5/5 - 3240165

## Classifications

### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	39121410
UNSPSC 19.0	39121410

## Approvals

### Approvals

Approvals

UL Listed / EAC

Ex Approvals

### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 327420
Nominal voltage UN	600 V		
Nominal current IN	12 A		
mm²/AWG/kcmil	20-16		

EAC		RU C- DE.BL08.B.00644
-----	--	--------------------------

Phoenix Contact 2021 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>