

## **Specification Sheet**

Part Number: 596-00834

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.

Aggressive adhesive ensures strong bond, even on powder coated surfaces.

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.



Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Metal Solar Placard, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", AA, Yellow, 5/pkg

Article Number 596-00834

Type CBACKFEDM5

Color Yellow (YE)

Quantity Per pack

_			_	_			
u	rn	A.	104	Des	cori	ntı	^n
	ıv	u	uCL	DC	36 I I	DLI	UII

Metal Solar Placards offer maximum durability and ease in code compliance. Perfect for solar applications, a special process seals metallic particles under a clear anodized layer, which results in markings that have been tested and rated to last up to 25 years in outdoor use, even in direct sunlight. Markers are designed to meet the latest National Electrical Code (NEC 2014), with pre-printed warning or caution messaging that conforms to Article 690, as well as ANSI guidelines. Pre-printed placards may be more acceptable to some local Authorities Having Jurisdiction (AHJs), who may have a preference for placard-style identification.

**Short Description** 

Metal Solar Placard, CAUTION PHOTOVOLTAIC SYSTEM

BACKFED, 4.12" x .75", AA, Yellow, 5/pkg

**Global Part Name** 

CBACKFEDM5-AA-YE

**Technical Description** 

4.0" X .75" Black text on an Yellow background that reads as:

"CAUTION PHOTOVOLTAIC SYSTEM CIRCUIT IS BACKFED." - 5

per pack.

**Local Order Number 2** 

Cross Reference = Paint Shield: 596-00797

Width W (Imperial)

4.125

Width W (Metric)

104.6

**Height H (Imperial)** 

.75

**Height H (Metric)** 

19.05

Material

Anodized Aluminum (AA)

**Material Shortcut** AA Adhesive Ultra High Bond Permanent Acrylic Adhesive **Halogen Free** No **Adhesive Operating Temperature** from +50°F (from +10°C) **Operating Temperature** -40°F to +203°F (-40°C to +95°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes **Certification/Specification** NEC2017 Yes Warranty (US) **Package Quantity (Imperial)** 5 Package Quantity (Metric) 5 **Customs Number** 7616995195

1

Labels per Column

Labels per Row

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions