





THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL





## NOTES:

MATERIAL:

HOUSING: GREEN THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 15µ GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C


**CURRENT RATING: 5A PER CONTACT** 

**CONTACT RESISTANCE:**  $25m\Omega$  MAX. INSULATOR RESISTANCE: 5000MΩ min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.





THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 627 ASSEMBLY					
DRAWN: C.B	DATE: AUG. 01/2018				
CHECKED:	DATE:				
SCALE: 1:1	SHEET 1 OF 1				
DRAWING NUMBER: 627-M37.	323-GN2 ISSUE				

SW REFERENCE NO.: 627 ASSEMBLY				
DRAWN: C.B		DATE: AUG. 01/2018		
CHECKED:		DATE:		
SCALE: 1:1		SHEET 1 OF 1		
DRAWING NUMBER:	627-M37-	323-GN2		ISSUE
PART NUMBER:	627-M37-323-GN2			1