



Click [here](#) for the 3D model.

| Dimensions | |
|------------|----------------|
| D | 25mm +1mm |
| L | 30mm +2mm |
| S | 10mm +/-0.5mm |
| LL | 5.8mm +/-1mm |
| F | 1.5mm +/-0.1mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 200 |

| General Information | |
|---------------------|--------------------------------|
| Series | ELH |
| Dielectric | Aluminum Electrolytic |
| Description | Snap-In, Aluminum Electrolytic |
| RoHS | Yes |
| Lead | 2 Pin |
| AEC-Q200 | No |

| Specifications | |
|-----------------------|--------------------------|
| Capacitance | 150 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 400 VDC, 450 VDC (Surge) |
| Temperature Range | -25/+85°C |
| Rated Temperature | 85°C |
| Life | 2000 Hrs |
| Dissipation Factor | 15% 120Hz 20C |
| Resistance | 1.327 Ohms (120 Hz 20°C) |
| Ripple Current | 1150 mAmps (120Hz) |
| Leakage Current | 1200 uA (5min 20°C) |